

2022

CATALOGUE

RST

RST

SPONSORED PRO RIDERS

	<i>BRAYDEN BARRETT-HAY</i>	 https://www.facebook.com/brayden.barretthay
	<i>GREG WATTS</i>	 https://www.facebook.com/greg.watts.146
	<i>JOSH HULT</i>	 https://www.facebook.com/Josh-Hult-540732435996299/
	<i>DEWAYNE TAYLOR</i>	 https://www.instagram.com/therealfourtyfour/
	<i>NIC HILTON</i>	 https://www.facebook.com/nic.hilton  https://www.instagram.com/nic_no_k/
	<i>JAY "CHUBBZ" MAGEE</i>	 https://www.instagram.com/feelgoodchubbz710/
	<i>DOUG MINOR</i>	 https://www.facebook.com/doug.minor.77
	<i>LUKAS RAINER</i>	 https://www.youtube.com/luxbiketv
	<i>NIKI GEORGIEV</i>	 https://www.facebook.com/nikigeorgiev305
	<i>FRED AUSTRUY</i>	 https://www.facebook.com/fred.austruy
	<i>RÉMY CARRA</i>	 https://www.facebook.com/remy.carra.3

	<i>JOÃO MENDES</i>	 https://www.facebook.com/joomendes
	<i>JAKUB VENCĽ</i>	 https://www.facebook.com/jakub.vencĽ/
	<i>DOMINIK PUFFER</i>	 https://www.facebook.com/dominik.puffer
	<i>MAX MEY</i>	 https://www.facebook.com/mey.maximilian
	<i>DANIEL PLENK</i>	 https://www.facebook.com/daniel.plenk.7
	<i>FREDERIK USBECK</i>	 https://www.facebook.com/frederik.usbeck
	<i>MARTI PEARCE</i>	 https://www.facebook.com/mcfly.pearce
	<i>CHARLIE CURRIE</i>	 https://www.instagram.com/charliecurriemtb/
	<i>GUSTAW DADELA</i>	 https://www.instagram.com/gustawdadela/
	<i>ALEC EKLÖW</i>	 https://www.instagram.com/ohnoinmalec/  https://www.youtube.com/channel/UChOqXUFIS-u-yjGx0vJJfBQ
	<i>RICHARD FERT</i>	 https://www.instagram.com/richardfert/

LOCAL TEAM SUPPORT

	<i>NSD RACING</i>	 https://www.instagram.com/nsdracing/
---	-------------------	---





RST TECHNOLOGY



OCR Platform

Low Speed Compression control with high speed compression shim stack.



OCRC Platform

Low Speed Compression control with high speed compression shim stack.



OCR Open-bath Compression Rebound Damping System

Fully adjustable hydraulic compression damping with lock-out, as well as externally adjustable rebound. This technology has been race proven and refined on the world circuit.



Tiny Remote Lockout

Smart Remote Lockout with complete new compact design . The shifter position can be adjusted vertically or horizontally with one bolt! No need to worry about any interference.



Remote Lock-out

This feature is available on any model featuring Compression/Lock-out adjustments. The remote has aluminium levers and a barrel adjuster on the cable to fine-tune your set up.



Rebound Adjustment

A hydraulic adjustable cartridge that lets you externally set the forks rebound.



Lock-out with Fixed-rebound

hydraulic cartridge damping system with lockout function and rebound damping.



Lock-out

hydraulic cartridge damping system with compression adjustment to lockout function.



Mechanical Lock-out

Mechanical lock-out system (not hydraulic).



Spring Pre-load

An adjustable top cap that lets a rider adjust the pre-load of the spring depending on rider weight and desired feel.



Post Lighting System

Front lamp holder integrated into the fork arch with two fixing bolts. Maintains the clean look of the fork arch with a plastic protection cover when the front lamp is not used.



CABLE ROUTING

Fork available with cable routing solution for a hub dynamo cable.

RST

CONTENTS


Product Overview / Color Options / Streerer Weight	7	► ROGUE 27.5/26 & TITAN 27.5/26	29	CROSS TREKKING
110 PLUS		► STORM 27.5/26 & VIBE 27.5	30	► VOGUE & VIV AIR
► ROGUE 110-15	10	► RENEGADE 26 FAT BKIE	31	► VOGUE E-15/9 & VIV AIR E-15/9
► TITAN 110-15 & VIBE 110-15	11	► GUIDE 26 & GUIDE 20 FAT BKIE	32	► VOLANT-15/9 & PLS BRACKET
► BLADE 110-15 NEW	12	► STEM SHOCK PAVEMENT	33	► VITA & NOVA
► FIRST 110-15/9 & AERIAL 110-15/9	13	XC		► NEON PLS & NEON
► ALPHA 110-15 & ALPHA 110-9	14	► REVEAL 29-15/27.5-15	35	► VERSE & URBAN
JUNIOR		► REVEAL 29/27.5/26	36	► PULSE 29-15 AIR/COIL & PULSE 29 AIR/COIL
► SNYPER 24 & IGNITE 24 NEW	16	► FIRST 29-15/27.5-15	37	► PULSE 27.5-15 AIR/COIL & PULSE 27.5 AIR/COIL
► FIRST 24-15 & FIRST 24	17	► FIRST 29/27.5/26	38	► AVALON 26 & SS-A8
► AERIAL 24 & SPEX 20	18	► AERIAL 29R-15/29-15/27.5R-15/27.5-15	39	► SS-A7 & SS-A2
► SPARK 20 NEW & CAPA 24/20	19	► AERIAL 29R/29/27.5R/27.5/26R/26	40	► SS-M7 & PILOT
CARGO		► OMEGA 29-15/27.5-15	41	AM PACKAGE
► PORTER 20 & GARY 20	21	► OMEGA 29/27.5/26	42	► AIR CARTRIDGE & AIR PUMP & GREASE
ADJUST SEATPOST		► BLAZE 29	43	► SPRING SEALS & ADJUSTER
► ELEV8 E & ELEV8 A2	23	► BLAZE 27.5-15/9	44	► SEAL KITS & WRENCH & CAPS
► ELEV8 H-S & ELEV8 A-S	24	► ALEX 26 & ANGEL 26	45	► SRL UPGRADE KIT & O-RING KIT
DH/FR/AM		► GILA 29/ 27.5/26 & CAPA 29/ 27.5/ 26 PAVEMENT	46	DIMENSIONS
► REBEL V2	26	DIRT JUMP		SPEC
► KILLAH 29 & KILLAH 27.5/26	27	► SPACE 26	48	RST GLOBAL
► STITCH 29 & STITCH 27.5/26	28	► SLOPE 27.5/26 & DIRT 26-15/9	49	RST DISTRIBUTORS




RST PRODUCTS OVERVIEW

		Down Hill	Free Ride	All Mountain	Fat Bike	Cargo	110-15	110-9	XC 29'er	XC 27.5
Taiwan Made	\$\$\$\$\$			REBEL						
			KILLAH							
				STITCH						
				ROGUE			ROGUE 110-15			
				TITAN	RENEGADE		TITAN 110-15			
				STORM						
	\$\$\$\$								REVEAL 29-15	REVEAL 27.5-15
									REVEAL 29	REVEAL 27.5
							F1RST 110-15	F1RST 110-9	F1RST 29-15	F1RST 27.5-15
									F1RST 29	F1RST 27.5
	\$\$\$						AERIAL 110-15	AERIAL 110-9	AERIAL 29 R	AERIAL27.5 R
China Made	\$\$			VIBE 27.5	GUIDE 26/20	PORTER 20	VIBE 110-15	ALPHA 110-9	OMEGA 29	OMEGA 27.5
						GARY 20	BLADE 110-15		BLAZE 29	BLAZE 27.5
							ALPHA 110-15		GILA 29	GILA 27.5

COLOR OPTIONS



DK-0011
GLOSS WHITE
(YS-701)



DK-0012
PEARL WHITE
(YS-775)



DK-8010
MATT BLACK
(YS-727)



DK-8011
SHINY BLACK
(YS-728)

<i>XC 26</i>	<i>Dirt Jump</i>	<i>Leisure Sport</i>	<i>Junior</i>	<i>Cross</i>	<i>Trekking</i>	<i>E-City</i>	<i>SEATPOST</i>	<i>Stem Shock</i>
	SPACE							
	SLOPE						ELEV 8 E	
			SNYPER 24					
			F1RST 24-15				ELEV 8 H	
REVEAL 26			SPEX 20			VOGUE E		
			F1RST 24	VOGUE		VIVAIR E		
F1RST 26			IGNITE 24			PULSE Air 29 / 27.5		
AERIAL 26 R			SPARK 20	VIV Air	SINGLE SHOCK (M)	PULSE Coil 29 / 27.5	ELEV 8 A	STEM SHOCK
AERIAL 26			AERIAL 24		SINGLE SHOCK (A)		ELEV8 A2	
OMEGA 26	DIRT	CAPA 29		VITA				
ALEX 26		CAPA 27.5		VOLANT				
GILA 26		CAPA 26	CAPA 24/20	AVALON				
ANGEL 26				NOVA	VERSE	NEON PLS		
				NEON	URBAN			

STEERER WEIGHT

<i>Steerer Tube</i>		<i>Length</i>	<i>Weight</i>
Aluminum 7050	28.6mm	260mm	176g
Aluminum 7050	1.5" Taper	260mm	186g
Hi-ten	28.6mm	260mm	326g
Hi-ten	25.4mm	260mm	290g
Hi-ten	1.5" Taper	260mm	415g



110 PLUS

Rider Frederik Usbeck Photographer Jan Alwers



ROGUE 110-15 mm

MODEL	AIR TRL	AIR	Air w/o Lockout
STEERER	1.5" Aluminum tapered steerer		
CROWN PITCH	150 mm		
STANCHION	34mm Aluminum Hard Anodize Black		
CASTING	Magnesium		
DROPOUT	15x110mm QR Axle		
FEATURE	Hydraulic Rebound adjust, Remote Lock-out, Air Spring	Hydraulic Compression, Rebound adjust, Lock-out, Air Spring"	Hydraulic Compression, Rebound adjust Air Spring
SYSTEM	OCR+(R), Air(L)		
TRAVEL (mm)	29" / 27.5"+: 120, 130, 140, 150, 160 mm		
BRAKE TYPE	Disc only		
WEIGHT (kgs) (w/ 200mm steerer)	2.35	2.33	2.33
Max Tire (w/o fender)	27.5"x3.0" or 29"x2.4"		





TITAN 110-15 mm


MODEL	Air TRL	Air	Air w/o Lockout
STEERER	1.5" Aluminum tapered steerer		
CROWN PITCH	150 mm		
STANCHION	34mm Aluminum Hard Anodize Black		
CASTING	Magnesium		
DROPOUT	15x110mm QR Axle		
FEATURE	Hydraulic Rebound adjust, Remote Lock-out, Air Spring	Hydraulic Compression, Rebound adjust, Lock-out, Air Spring	Hydraulic Compression, Rebound adjust, Air Spring
SYSTEM	OCR(R), Air(L)		
TRAVEL (mm)	29" / 27.5"+: 120, 130, 140, 150 mm		
BRAKE TYPE	Disc only		
WEIGHT (kgs) (w/ 200mm steerer)	2.40	2.38	2.38
Max Tire (w/o fender)	27.5"x3.0 or 29"x2.4		



AIR/COIL

VIBE 110-15 mm

MODEL	RA	RL	TNL
STEERER	1.5" Steel tapered steerer		
CROWN PITCH	150 mm		
STANCHION	34mm Steel QPQ black		
CASTING	Magnesium		
DROPOUT	15x110mm Bolt Axle		
FEATURE	Hydraulic Rebound adjust	Hydraulic Remote Lock-Out	Hydraulic Lock-Out
SYSTEM	Oil(R), Coil(L) / Oil(R), Air(L)		
TRAVEL (mm)	29" / 27.5"+: 100, 120, 130, 140 mm		
BRAKE TYPE	Disc Only		
WEIGHT (kgs) (w/ 200mm steerer)	Air: 3.27 Coil: 3.47	Air: 3.36 Coil: 3.56	Air: 3.30 Coil: 3.50
Max Tire (w/o fender)	27.5"x3.0" or 29"x2.4"		



NEW
2022 ITEM



BLADE 110-15 mm

MODEL	RL	TNL	AIR-RL	AIR-TNL
STEERER	1.5" Steel tapered steerer			
CROWN PITCH	140 mm			
STANCHION	34mm Steel QPQ black			
CASTING	Aluminum			
DROPOUT	15x110mm Bolt Axle			
FEATURE	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Hydraulic Remote Lock-Out Air Spring	Hydraulic Lock-Out Air Spring
SYSTEM	Oil(R), Coil(L)		Oil(R), Air(L)	
TRAVEL (mm)	29" / 27.5"+: 120, 130, 140, 150 mm			
BRAKE TYPE	Disc Only			
"WEIGHT (kgs) (w/ 200mm steerer)"	3.06	3.00	2.86	2.80
Max Tire (w/o fender)	27.5"x2.8" or 29"x2.6"			



M5&M6 headlight bracket option



110 PLUS



FIRST 110-15/9_{mm}

MODEL	110-15 Air TRL	110-15 Air	110-9 Air TRL	110-9 Air
STEERER	28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)			
CROWN PITCH	140 mm			
STANCHION	32mm Aluminum Hard Anodize Black			
CASTING	Magnesium			
DROPOUT	15x110mm Bolt Axle		9x110mm Open Dropout	
FEATURE	Hydraulic Rebound adjust, Remote Lock- out, Air Spring	Hydraulic Compression, Rebound adjust, Lock- out, Air Spring	Hydraulic Rebound adjust, Remote Lock- out, Air Spring	Hydraulic Compression, Rebound adjust, Lock- out, Air Spring
SYSTEM	OCR(R),Air(L)			
TRAVEL (mm)	29" / 27.5"+/27.5"/ 26": 80, 100, 120 mm			
BRAKE TYPE	Disc only			
WEIGHT (kgs) (w/ 200mm steerer)	2.12	2.10	1.95	1.93
Max Tire (w/o fender)	29"x2.6" or 27.5"x2.8" or 26"x3.0"			



AERIAL 110-15/9_{mm}

MODEL	RL	TNL	MLC
STEERER	28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)		
CROWN PITCH	140 mm		
STANCHION	32mm Steel QPQ black		
CASTING	Magnesium		
DROPOUT	15x110mm Bolt Axle 9x110mm Open Dropout		
FEATURE	Hydraulic Remote Lock- out, Air Spring	Hydraulic Lock- out, Air Spring	Mechanical Lock-out, Air Spring
SYSTEM	Oil (R), Air(L)		Air(L)
TRAVEL (mm)	29" / 27.5"+/27.5"/ 26": 80, 100, 120 mm		
BRAKE TYPE	Disc only		
WEIGHT (kgs) (w/ 200mm steerer)	2.55	2.47	2.27
Max Tire (w/o fender)	29"x2.6" or 27.5"x2.8" or 26"x3.0"		



ALPHA 110-15_{mm}

MODEL	RL	TNL	RA	MLC	T
STEERER	28.6mm Steel (Optional 1.5" Steel tapered steerer)				
CROWN PITCH	140 mm				
STANCHION	32mm Steel CP Finish				
CASTING	Magnesium				
DROPOUT	15x110mm Bolt Axle				
FEATURE	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Hydraulic Rebound adjust	Mechanical Lock-Out	Preload Adjust
SYSTEM	Oil(R), Coil(L)			Coil	
TRAVEL (mm)	29" / 27.5+: 80, 100, 120, 130, 135 mm				
BRAKE TYPE	Disc Only				
WEIGHT (kgs) (w/ 200mm steerer)	2.65	2.57	2.54	2.34	2.34
Max Tire (w/o fender)	27.5"x2.8" or 29"x2.6"				



ALPHA 110-9_{mm}

MODEL	RL	TNL	RA	MLC	T
STEERER	28.6mm Steel (Optional 1.5" Steel tapered steerer)				
CROWN PITCH	140 mm				
STANCHION	32mm Steel CP Finish				
CASTING	Magnesium				
DROPOUT	9x110mm Open Dropout				
FEATURE	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Hydraulic Rebound adjust	Mechanical Lock-Out	Preload Adjust
SYSTEM	Oil(R), Coil(L)			Coil	
TRAVEL (mm)	29" / 27.5+ : 80, 100, 120, 130, 140 mm 27.5" / 26" : 80, 100, 120, 130, 140 mm				
BRAKE TYPE	Disc Only				
WEIGHT (kgs) (w/ 200mm steerer)	2.46	2.40	2.37	2.17	2.17
Max Tire (w/o fender)	29" / 27.5"+ : 27.5"x2.8" or 29"x2.4" 27.5" / 26" : 27.5"x2.6" or 26"x3.0"				

110 PLUS



JUNIOR



SNYPER 24

MODEL	24 TRL	24
STEERER	28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)	
CROWN PITCH	130 mm	
STANCHION	32mm Aluminum Hard Anodize Black	
CASTING	Magnesium	
DROPOUT	9mm Open Dropout	
FEATURE	Hydraulic Rebound adjust, Remote Lock-out, Air Spring	Hydraulic Compression, Rebound adjust, Lock-out, Air Spring
SYSTEM	OCR(R), Air(L)	
TRAVEL (mm)	24": 60, 70, 80, 100, 120 mm	
BRAKE TYPE	Disc Only	
WEIGHT (kgs) (w/ 200mm steerer)	1.87	1.85
Max Tire (w/o fender)	24"X2.2"	




NEW
2022 ITEM



IGNITE 24

MODEL	RL	TNL	MLC
STEERER	28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)		
CROWN PITCH	130 mm		
STANCHION	32mm Steel QPQ black		
CASTING	Magnesium		
DROPOUT	9mm Open Dropout		
FEATURE	Hydraulic Remote Lock-out, Air Spring	Hydraulic Lock-out, Air Spring	Mechanical Lock-out, Air Spring
SYSTEM	Oil(R), Air(L)		Air
TRAVEL (mm)	24": 80, 100, 120 mm		
BRAKE TYPE	Disc Only		
WEIGHT (kgs) (w/ 200mm steerer)	2.31	2.25	2.05
Max Tire (w/o fender)	24"X2.2"		

JUNIOR



FIRST 24-15_{mm}

MODEL	24-15 TRL	24-15
STEERER	28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)	
CROWN PITCH	130 mm	
STANCHION	30mm Aluminum Hard Anodize Black	
CASTING	Magnesium	
DROPOUT	15mm QR Axle	
FEATURE	Hydraulic Rebound adjust, Remote Lock-out, Air Spring	Hydraulic Compression, Rebound adjust, Lock-out, Air Spring
SYSTEM	OCR(R), Air(L)	
TRAVEL (mm)	24": 80, 100, 120 mm	
BRAKE TYPE	Disc Only	
WEIGHT (kgs) (w/ 200mm steerer)	1.92	1.90
Max Tire (w/o fender)	24"X2.6"	



F1RST 24

MODEL	24 TRL	24
STEERER	28.6mm Aluminum	
CROWN PITCH	125 mm	
STANCHION	28.6mm Aluminum Hard Anodize Black	
CASTING	Magnesium	
DROPOUT	9mm Open Dropout	
FEATURE	Hydraulic Rebound adjust, Remote Lock-out, Air Spring	Hydraulic Compression, Rebound adjust, Lock-out, Air Spring
SYSTEM	OCR(R), Air(L)	
TRAVEL (mm)	24": 60 mm	
BRAKE TYPE	Disc Only	
WEIGHT (kgs) (w/ 200mm steerer)	1.62	1.60
Max Tire (w/o fender)	24"X2.2"	



AERIAL 24

MODEL	RL	TNL	MLC
STEERER	28.6mm Aluminum		
CROWN PITCH	125 mm		
STANCHION	28.6mm Steel QPQ black		
CASTING	Magnesium		
DROPOUT	9mm Open Dropout		
FEATURE	Hydraulic Remote Lock-out, Air Spring	Hydraulic Lock-out, Air Spring	Mechanical Lock-out, Air Spring
SYSTEM	Oil(R), Air(L)		Air
TRAVEL (mm)	24": 60 mm		
BRAKE TYPE	Disc Only		
WEIGHT (kgs) (w/ 200mm steerer)	1.99	1.93	1.73
Max Tire (w/o fender)	24"X2.2"		



SPEX 20-15/9_{mm}

MODEL	9 TRL	9 AIR	15 TRL	15 AIR
STEERER	28.6mm Aluminum			
CROWN PITCH	125 mm			
STANCHION	30mm Aluminum Hard Anodize Black			
CASTING	Magnesium			
DROPOUT	9mm Open Dropout		15mm Bolt Axle	
FEATURE	Hydraulic Rebound adjust, Remote Lock-out, Air Spring	Hydraulic Compression, Rebound adjust, Lock-out, Air Spring	Hydraulic Rebound adjust, Remote Lock-out, Air Spring	Hydraulic Compression, Rebound adjust, Lock-out, Air Spring
SYSTEM	OCR(R), Air(L)		OCR(R), Air(L)	
TRAVEL (mm)	20": 60, 80, 100 mm			
BRAKE TYPE	Disc or Disc & V-brake			
WEIGHT (kgs) (w/ 200mm steerer)	1.67	1.65	1.72	1.70
Max Tire (w/o fender)	20" X2.4"			

JUNIOR

NEW
2022 ITEM



SPARK 20

MODEL	15 RL	15 TNL	15 MLC	9 RL	9 TNL	9 MLC
STEERER	28.6mm Aluminum					
CROWN PITCH	125 mm					
STANCHION	30mm Steel QPQ black					
CASTING	Magnesium					
DROPOUT	15mm Bolt Axle			9mm Open Dropout		
FEATURE	Hydraulic Remote Lock-out, Air Spring	Hydraulic Lock-out, Air Spring	Mechanical Lock-out, Air Spring	Hydraulic Remote Lock-out, Air Spring	Hydraulic Lock-out, Air Spring	Mechanical Lock-out, Air Spring
SYSTEM	Oil(R), Air(L)		Air	Oil(R), Air(L)		Air
TRAVEL (mm)	20": 60, 80, 100 mm					
BRAKE TYPE	Disc or Disc & V-brake					
WEIGHT (kgs) (w/ 200mm steerer)	2.31	2.25	2.05	2.26	2.20	2.00
Max Tire (w/o fender)	20"X2.4"					



CAPA 24/20

MODEL	MLC 24		T24	T20
STEERER	28.6 / 25.4mm Steel			
CROWN PITCH	120 mm			
STANCHION	25.4mm Steel CP Finish			
CASTING	Aluminum			
DROPOUT	9mm Open Dropout			
FEATURE	Mechanical Lock-Out	Preload Adjust		
SYSTEM	Coil			
TRAVEL (mm)	24" :50 mm	24" :30, 50 mm	20":30,50 mm	
BRAKE TYPE	Disc or Disc & V-brake			
WEIGHT (kgs) (w/ 200mm steerer)	1.93	1.84	1.75	
Max Tire (w/o fender)	24"X2.2"			20"X2.2"



OLD SCHOOL

CARGO



PORTER 20

MODEL	15T	9T
STEERER	28.6mm Cr-mo steel	
CROWN PITCH	125 mm	
STANCHION	30mm Steel CP Finish	
CASTING	Magnesium	
DROPOUT	15mm Bolt Axle	9mm Open Dropout
FEATURE	Preload Adjust	
SYSTEM	Coil	
TRAVEL (mm)	20": 40, 60, 80 mm	
BRAKE TYPE	Disc or Disc & V-brake	
WEIGHT (kgs) (w/ 200mm steerer)	2.14	2.09
Max Tire (w/o fender)	20"x2.4"	



GARY 20

MODEL	20T
STEERER	28.6mm Steel
CROWN PITCH	125 mm
STANCHION	28.6mm Steel CP Finish
CASTING	Aluminum
DROPOUT	9mm Open Dropout
FEATURE	Preload Adjust
SYSTEM	Coil
TRAVEL (mm)	20": 50 mm
BRAKE TYPE	Disc & V-brake
WEIGHT (kgs) (w/ 200mm steerer)	2.17
Max Tire (w/o fender)	20"x2.6"



ADJUSTABLE SEATPOST

Rider Dominik Puffer Photographer Benjamin Jicha



ELEV8 E

MODEL	ELEV 8 E
FUNCTION	Hydraulic Height Adjustment Seat Post
TRAVEL	100, 125, 150 mm
FEATURE	Electronic Remote Operated
DIAMETER	30.9/ 31.6 mm
LENGTH (TRAVEL/ LENGTH)	TR100: 420mm TR125: 445mm TR150: 510mm
WEIGHT	700-710g (30.9mm) 710-720g (31.6mm)



ELEV8 A2

MODEL	ELEV 8 A2
FUNCTION	Air Height Adjustment Seat Post
TRAVEL	80, 100, 125, 150, 170 mm
FEATURE	Stealth Air Remote Operated
DIAMETER	30.9/ 31.6 mm
LENGTH (TRAVEL/ LENGTH)	TR 80: 306mm TR100: 364mm TR125: 413mm TR150: 463mm TR170: 496mm
WEIGHT	635-645g (30.9mm) 645-655g (31.6mm)



ELVE8 H-S

MODEL	ELEV 8 H	ELEV 8 H-S
FUNCTION	Hydraulic Height Adjustment Seat Post	
TRAVEL	100, 125, 150 mm	
FEATURE	External Hydraulic Remote Operated	Stealth Hydraulic Remote Operated
DIAMETER	30.9/ 31.6 mm	
LENGTH (TRAVEL/ LENGTH)	TR100: 365mm TR125: 414mm TR150: 439mm	
WEIGHT	735-745g (30.9mm) 745-755g (31.6mm)	685-695g (30.9mm) 695-705g (31.6mm)



ELEV8 A-S

MODEL	ELEV 8 A	ELEV 8 A-S
FUNCTION	Air Height Adjustment Seat Post	
TRAVEL	100, 125, 150 mm	
FEATURE	External Air Remote Operated	Stealth Air Remote Operated
DIAMETER	30.9/ 31.6 mm	
LENGTH (TRAVEL/ LENGTH)	TR100: 344mm TR125: 418mm TR150: 444mm	
WEIGHT	685-695g (30.9mm) 695-705g (31.6mm)	635-645g (30.9mm) 645-655g (31.6mm)



DH/FR/AM

Steep descents and technical terrain require top-performance from both riders and their equipment. Durable construction without a major weight penalty and high performance damping systems distinguish these forks ready for the trail, bike park, even a World Cup course.

Rider Frederik Usbeck Photographer Jan Alwers



REBEL V2

MODEL	AIR TRL	AIR	Air w/o Lockout
STEERER	1.5" Aluminum tapered steerer		
CROWN PITCH	140 mm		
STANCHION	32mm Aluminum Hard Anodize Black		
CASTING	Magnesium		
DROPOUT	20x110mm Boost Bolt Axle (Optional 15x110mm Bolt Axle)		
FEATURE	Hydraulic Rebound adjust, Remote Lock-out, Air Spring	Hydraulic Compression, Rebound adjust, Lock-out, Air Spring	Hydraulic Compression, Rebound adjust, Air Spring
SYSTEM	OCR+(R), Air(L)		
TRAVEL (mm)	29":80, 100, 130 mm 27.5"+:100, 130, 140, 150 mm		
BRAKE TYPE	Disc only		
WEIGHT (kgs) (w/ 200mm steerer)	29": 2.25 27.5": 2.35	29": 2.23 27.5": 2.33	29": 2.23 27.5": 2.33
Max Tire (w/o fender)	27.5"x3.0" or 29"x2.4"		





KILLAH 29

MODEL	COIL	AIR
STEERER	28.6mm Aluminum	
CROWN PITCH	145 mm-Dual	
STANCHION	38mm Aluminum Hard Anodize Black	
CASTING	Magnesium	
DROPOUT	20x110mm Boost Bolt Axle	
FEATURE	Hydraulic Compression, Rebound adjust	Hydraulic Compression, Rebound adjust, Air Spring
SYSTEM	OCR+(R), Coil(L)	OCR+(R), Air(L)
TRAVEL (mm)	29": 200 mm	
BRAKE TYPE	Disc only	
WEIGHT (kgs) (w/ 200mm steerer)	3.25	3.05
Max Tire (w/o fender)	29"x2.6"	




KILLAH 27.5/26

MODEL	COIL	AIR
STEERER	28.6mm Aluminum	
CROWN PITCH	138 mm-Dual	
STANCHION	36mm Aluminum Hard Anodize Black	
CASTING	Magnesium	
DROPOUT	20mm Bolt Axle	
FEATURE	Hydraulic Compression, Rebound adjust	Hydraulic Compression, Rebound adjust, Air Spring
SYSTEM	OCR+(R), Coil(L)	OCR+(R), Air(L)
TRAVEL (mm)	27.5" / 26": 200 mm	
BRAKE TYPE	Disc Only	
WEIGHT (kgs) (w/ 200mm steerer)	27.5": 3.22 26": 3.20	27.5": 3.02 26": 3.00
Max Tire (w/o fender)	27.5"x2.4" or 26"x2.4"	



STITCH 29

MODEL	COIL	AIR
STEERER	1.5" Aluminum tapered steerer	
CROWN PITCH	145 mm	
STANCHION	38mm Aluminum Hard Anodize Black	
CASTING	Magnesium	
DROPOUT	20x110mm Boost Bolt Axle or 15x110mm Bolt Axle	
FEATURE	Hydraulic Compression, Rebound adjust	Hydraulic Compression, Rebound adjust, Air Spring
SYSTEM	OCR+(R), Coil(L)	OCR+(R), Air(L)
TRAVEL (mm)	29": 160, 170, 180 mm	
BRAKE TYPE	Disc Only	
WEIGHT (kgs) (w/ 200mm steerer)	2.88	2.68
Max Tire (w/o fender)	29"x2.6"	



STITCH 27.5/26

MODEL	COIL	AIR
STEERER	28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)	
CROWN PITCH	138 mm	
STANCHION	36mm Aluminum Hard Anodize Black	
CASTING	Magnesium	
DROPOUT	20mm QR Axle	
FEATURE	Hydraulic Compression, Rebound adjust	Hydraulic Compression, Rebound adjust, Air Spring
SYSTEM	OCR+(R), Coil(L)	OCR+(R), Air(L)
TRAVEL (mm)	27.5" / 26": 160, 170, 180 mm	
BRAKE TYPE	Disc Only	
WEIGHT (kgs) (w/ 200mm steerer)	27.5": 2.57 26": 2.55	27.5": 2.28 26": 2.26
Max Tire (w/o fender)	27.5"x2.4" or 26"x2.4"	



ROGUE 27.5/26

MODEL	Air TRL	Air	Air w/o Lockout
STEERER	28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)		
CROWN PITCH	130 mm		
STANCHION	34mm Aluminum Hard Anodize Black		
CASTING	Magnesium		
DROPOUT	15mm QR Axle		
FEATURE	Hydraulic Rebound adjust, Remote Lock-out, Air Spring	Hydraulic Compression, Rebound adjust, Lock-out, Air Spring	Hydraulic Compression, Rebound adjust, Air Spring
SYSTEM	OCR+(R), Air(L)		
TRAVEL (mm)	27.5" / 26": 140, 150, 160 mm		
BRAKE TYPE	Disc Only		
WEIGHT (kgs) (w/ 200mm steerer)	27.5": 2.13 26": 2.00	27.5": 2.11 26": 1.98	27.5": 2.11 26": 1.98
Max Tire (w/o fender)	27.5"x2.4" or 26"x2.4"		



TITAN 27.5/26

MODEL	Air TRL	Air	Air w/o Lockout
STEERER	28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)		
CROWN PITCH	130 mm		
STANCHION	34mm Aluminum Hard Anodize Black		
CASTING	Magnesium		
DROPOUT	15mm QR Axle		
FEATURE	Hydraulic Rebound adjust, Remote Lock-out, Air Spring	Hydraulic Compression, Rebound adjust, Lock-out, Air Spring	Hydraulic Compression, Rebound adjust, Air Spring
SYSTEM	OCR(R), Air(L)		
TRAVEL (mm)	27.5" / 26": 140, 150 mm		
BRAKE TYPE	Disc Only		
WEIGHT (kgs) (w/ 200mm steerer)	27.5": 2.18 26": 2.05	27.5": 2.16 26": 2.03"	27.5": 2.16 26": 2.03"
Max Tire (w/o fender)	27.5"x2.4" or 26"x2.4"		



STORM 27.5/26

MODEL	RA
STEERER	28.6mm Cr-mo Steel (Optional 1.5" Aluminum tapered steerer)
CROWN PITCH	138 mm
STANCHION	36mm Steel QPQ Black
CASTING	Magnesium
DROPOUT	20mm QR Axle
FEATURE	Hydraulic Rebound adjust
SYSTEM	Oil(R), Coil(L)
TRAVEL (mm)	27.5" / 26": 160, 170, 180 mm
BRAKE TYPE	Disc Only
WEIGHT (kgs) (w/ 200mm steerer)	27.5": 3.34 26": 3.32
Max Tire (w/o fender)	27.5"x2.4" or 26"x2.4"



VIBE 27.5

MODEL	RA	RL	TNL	AIR-RA	AIR-RL	AIR-TNL
STEERER	1.5" Steel tapered steerer					
CROWN PITCH	130 mm					
STANCHION	34mm Steel QPQ black					
CASTING	Magnesium					
DROPOUT	15mm Bolt Axle					
FEATURE	Hydraulic Rebound adjust	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Hydraulic Rebound adjust Air Spring	Hydraulic Remote Lock-Out Air Spring	Hydraulic Lock-Out Air Spring
SYSTEM	Oil(R), Coil(L)			Oil(R), Air(L)		
TRAVEL (mm)	27.5": 130, 140 mm					
BRAKE TYPE	Disc Only					
WEIGHT (kgs) (w/ 200mm steerer)	3.14	3.23	3.17	2.88	2.97	2.91
Max Tire (w/o fender)	27.5"x2.4"					





RENEGADE 26

MODEL	Air TRL	Air	TNL
STEERER	28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)		1.5" Steel tapered steerer
CROWN PITCH	190 mm		
STANCHION	32mm Aluminum Hard Anodize Black		32mm Steel CP Finish
CASTING	Magnesium		
DROPOUT	15x150mm QR Axle		
FEATURE	Hydraulic Rebound adjust, Remote Lock-out, Air Spring	Hydraulic Compression, Rebound adjust, Lock-out, Air Spring	Hydraulic Lock-Out
SYSTEM	OCR(R), Air(L)		Oil(R), Coil(L)
TRAVEL (mm)	26": 80, 100, 120 mm		
BRAKE TYPE	Disc Only		
WEIGHT (kgs) (w/ 200mm steerer)	2.22	2.20	3.00
Max Tire (w/o fender)	26"x4.0"		





GUIDE 26

MODEL	AIR-TNL	AIR-MLC	TNL	MLC	T
STEERER	28.6mm Steel (Optional 1.5" Steel tapered steerer)				
CROWN PITCH	180 mm				
STANCHION	32mm Steel CP Finish				
CASTING	Aluminum				
DROPOUT	9x135mm Open Dropout				
FEATURE	Hydraulic Lock-Out Air Spring	Mechanical Lock-Out Air Spring	Hydraulic Lock-Out	Mechanical Lock-Out	Preload Adjust
SYSTEM	Oil(R), Air(L)	Air	Oil(R), Coil(L)	Coil	
TRAVEL (mm)	26": 70, 80, 95 mm				
BRAKE TYPE	Disc Only				
WEIGHT (kgs) (w/ 200mm steerer)	3.52	3.37	3.62	3.47	3.32
Max Tire (w/o fender)	26"x4.6"				



GUIDE 20

MODEL	AIR-TNL	AIR-MLC	TNL	MLC	T
STEERER	28.6mm Steel (Optional 1.5" Steel tapered steerer)				
CROWN PITCH	180 mm				
STANCHION	32mm Steel CP Finish				
CASTING	Aluminum				
DROPOUT	9x135mm Open Dropout				
FEATURE	Hydraulic Lock-Out Air Spring	Mechanical Lock-Out Air Spring	Hydraulic Lock-Out	Mechanical Lock-Out	Preload Adjust
SYSTEM	Oil(R), Air(L)	Air	Oil(R), Coil(L)	Coil	
TRAVEL (mm)	20": 45, 60 mm				
BRAKE TYPE	Disc Only				
WEIGHT (kgs) (w/ 200mm steerer)	3.27	3.12	3.37	3.22	3.07
Max Tire (w/o fender)	20"x4.6"				

PAVEMENT

STEM SHOCK

MODEL	STEM SHOCK
Adjustable angle	+4°, 0°, -4°
Travel	20 mm
Features	Angle adjust spacer option for the stem
Diameter	fit into inner diameter ≥ 24.5mm steerer
Length	Suspension system will add 50mm of height to the steer tube
Weight	0.38





XC

Lightweight and efficient suspension from 80mm to 120mm distinguish the XC and touring lineups. Forks with a perfectly balanced mixture of comfort, performance and trail control ready for enjoying your local trail network to competing in the toughest race events.



REVEAL 15_{mm} 29/27.5

MODEL	15 AIR TRL	15 AIR
STEERER	28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)	
CROWN PITCH	130 mm	
STANCHION	32mm Aluminum Hard Anodize Black	
CASTING	Magnesium	
DROPOUT	15mm QR Axle	
FEATURE	Hydraulic Rebound adjust, Remote Lock-out, Air Spring	Hydraulic Compression, Rebound adjust, Lock-out, Air Spring
SYSTEM	OCR+(R), Air(L)	
TRAVEL (mm)	29"/27.5": 80, 100, 120 mm	
BRAKE TYPE	Disc Only	
WEIGHT (kgs) (w/ 200mm steerer)	29": 1.82 27.5": 1.78	29": 1.80 27.5": 1.76
Max Tire (w/o fender)	29"x2.6" or 27.5"x2.6"	





REVEAL 9_{mm} 29/27.5/26

MODEL	9 AIR TRL	9 AIR
STEERER	28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)	
CROWN PITCH	130 mm	
STANCHION	32mm Aluminum Hard Anodize Black	
CASTING	Magnesium	
DROPOUT	9mm Open Dropout	
FEATURE	Hydraulic Rebound adjust, Remote Lock-out, Air Spring	Hydraulic Compression, Rebound adjust, Lock-out, Air Spring
SYSTEM	OCR+(R), Air(L)	
TRAVEL (mm)	29"/27.5"/26": 80, 100, 120 mm	
BRAKE TYPE	Disc Only (26" has Disc & V-brake version option)	
WEIGHT (kgs) (w/ 200mm steerer)	29": 1.78 27.5": 1.73 26": 1.53	29": 1.75 27.5": 1.71 26": 1.51
Max Tire (w/o fender)	29"x2.6" or 27.5"x2.6" or 26"x2.4"	





FIRST 15_{mm} 29/27.5

MODEL	15 AIR TRL	15 AIR
STEERER	28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)	
CROWN PITCH	130 mm	
STANCHION	32mm Aluminum Hard Anodize Black	
CASTING	Magnesium	
DROPOUT	15mm QR Axle	
FEATURE	Hydraulic Rebound adjust, Remote Lock-out, Air Spring	Hydraulic Compression, Rebound adjust, Lock-out, Air Spring
SYSTEM	OCR(R), Air(L)	
TRAVEL (mm)	29"/27.5": 80, 100, 120 mm	
BRAKE TYPE	Disc Only	
WEIGHT (kgs) (w/ 200mm steerer)	29": 2.15 27.5": 2.10	29": 2.13 27.5": 2.08
Max Tire (w/o fender)	29"x2.6" or 27.5"x2.6"	





FIRST 9_{mm} 29/27.5/26

MODEL	9 AIR TRL	9 AIR
STEERER	28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)	
CROWN PITCH	130 mm	
STANCHION	32mm Aluminum Hard Anodize Black	
CASTING	Magnesium	
DROPOUT	9mm Open Dropout	
FEATURE	Hydraulic Rebound adjust, Remote Lock-out, Air Spring	Hydraulic Compression, Rebound adjust, Lock-out, Air Spring
SYSTEM	OCR(R), Air(L)	
TRAVEL (mm)	29"/27.5"/26": 80, 100, 120 mm	
BRAKE TYPE	Disc Only (26" has Disc & V-brake version option)	
WEIGHT (kgs) (w/ 200mm steerer)	29": 2.10 27.5": 2.05 26": 1.82	29": 2.08 27.5": 2.03 26": 1.80
Max Tire (w/o fender)	29"x2.6" or 27.5"x2.6" or 26"x2.4"	





AERIAL 15_{mm} 29/27.5

MODEL	15 RL-R	15 TNL-R	15 RL	15 TNL	15 MLC
STEERER	28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)				
CROWN PITCH	130 mm				
STANCHION	32mm Steel QPQ Black				
CASTING	Magnesium				
DROPOUT	15mm Bolt Axle				
FEATURE	Hydraulic Rebound Adjust, Remote Lock-out, Air Spring	Hydraulic Rebound Adjust, Lock-out, Air Spring	Hydraulic Remote Lock-out, Air Spring	Hydraulic Lock-out, Air Spring	Mechanical Lock-out, Air Spring
SYSTEM	Oil(R), Air(L)				Air(L)
TRAVEL (mm)	29"/27.5": 80, 100, 120 mm				
BRAKE TYPE	Disc Only				
WEIGHT (kgs) (w/ 200mm steerer)	29": 2.52 27.5": 2.47	29": 2.46 27.5": 2.41	29": 2.46 27.5": 2.41	29": 2.40 27.5": 2.35	29": 2.20 27.5": 2.15
Max Tire (w/o fender)	29"x2.6" or 27.5"x2.6"				





AERIAL 9_{mm} 29/27.5/26

MODEL	9 RL-R	9 TNL-R	9 RL	9 TNL	9 MLC
STEERER	28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)				
CROWN PITCH	130 mm				
STANCHION	32mm Steel QPQ Black				
CASTING	Magnesium				
DROPOUT	9mm Open Dropout				
FEATURE	Hydraulic Rebound Adjust, Remote Lock-out, Air Spring*	Hydraulic Rebound Adjust, Lock-out, Air Spring	Hydraulic Remote Lock-out, Air Spring	Hydraulic Lock-out, Air Spring	Mechanical Lock-out, Air Spring*
SYSTEM	Oil(R), Air(L)				Air(L)
TRAVEL (mm)	29"/27.5"/26": 80, 100, 120 mm				
BRAKE TYPE	Disc Only (26" has Disc & V-brake version option)				
WEIGHT (kgs) (w/ 200mm steerer)	29": 2.47 27.5": 2.42 26": 2.37	29": 2.41 27.5": 2.36 26": 2.31	29": 2.41 27.5": 2.36 26": 2.31	29": 2.35 27.5": 2.30 26": 2.25	29": 2.15 27.5": 2.10 26": 2.02
Max Tire (w/o fender)	29"x2.6" or 27.5"x2.6" or 26"x2.4"				





OMEGA 15_{mm} 29/27.5

MODEL	15 RA	15 RL	15 TNL	15 MLC	15 T
STEERER	28.6mm Steel (Optional 1.5" Steel tapered steerer)				
CROWN PITCH	130 mm				
STANCHION	32mm Steel CP Finish				
CASTING	Magnesium				
DROPOUT	15mm Bolt Axle				
FEATURE	Hydraulic Rebound adjust	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Mechanical Lock-Out	Preload Adjust
SYSTEM	Oil(R), Coil(L)			Coil	
TRAVEL (mm)	29"/27.5": 80, 100, 120 mm				
BRAKE TYPE	Disc Only				
WEIGHT (kgs) (w/ 200mm steerer)	29": 2.49 27.5": 2.32	29": 2.60 27.5": 2.41	29": 2.52 27.5": 2.35	29": 2.29 27.5": 2.12	29": 2.29 27.5": 2.12
Max Tire (w/o fender)	29" x 2.6" or 27.5" x 2.6" or 26" x 2.4"				





OMEGA 9_{mm} 29/27.5/26

MODEL	9 RA	9 RL	9 TNL	9 MLC	9 T
STEERER	28.6mm Steel (Optional 1.5" Steel tapered steerer)				
CROWN PITCH	130 mm				
STANCHION	32mm Steel CP Finish				
CASTING	Magnesium				
DROPOUT	9mm Open Dropout				
FEATURE	Hydraulic Rebound adjust	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Mechanical Lock-Out	Preload Adjust
SYSTEM	Oil(R), Coil(L)			Coil	
TRAVEL (mm)	29"/27.5"/26": 80, 100, 120 mm				
BRAKE TYPE	Disc Only (26" has Disc & V-brake version option)				
WEIGHT (kgs) (w/ 200mm steerer)	29": 2.44 27.5": 2.27 26": 2.5	29": 2.55 27.5": 2.36 26": 2.61	29": 2.47 27.5": 2.30 26": 2.53	29": 2.29 27.5": 2.07 26": 2.30	29": 2.29 27.5": 2.07 26": 2.30
Max Tire (w/o fender)	29" x 2.6" or 27.5" x 2.6" or 26" x 2.4"				





BLAZE 29

MODEL	RA		RL	TNL	MLC	T
STEERER	28.6mm Steel (Optional 1.5" Steel tapered steerer)					
CROWN PITCH	130 mm					
STANCHION	30mm Steel CP Finish					
CASTING	Aluminum					
DROPOUT	9mm Open Dropout					
FEATURE	Hydraulic Rebound adjust	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Mechanical Lock-Out	Preload Adjust	
SYSTEM	Oil(R), Coil(L)				Coil	
TRAVEL (mm)	29": 80, 100, 120 mm					
BRAKE TYPE	Disc Only					
WEIGHT (kgs) (w/ 200mm steerer)	2.81	2.90	2.84	2.61	2.61	
Max Tire (w/o fender)	29" x 2.6"					





BLAZE 27.5-15/9_{mm}

MODEL	15 RA	15 RL	15 TNL	15 MLC	15 T	9 RA	9 RL	9 TNL	9 MLC	9 T
STEERER	28.6mm Steel									
CROWN PITCH	130 mm									
STANCHION	30mm Steel CP Finish									
CASTING	Aluminum									
DROPOUT	15mm Bolt Axle					9mm Open Dropout				
FEATURE	Hydraulic Rebound adjust	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Mechanical Lock-Out	Preload Adjust	Hydraulic Rebound adjust	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Mechanical Lock-Out	Preload Adjust
SYSTEM	Oil(R), Coil(L)			Coil		Oil(R), Coil(L)			Coil	
TRAVEL (mm)	27.5": 80, 100, 120 mm									
BRAKE TYPE	Disc Only									
WEIGHT (kgs) (w/ 200mm steerer)	2.78	2.87	2.81	2.56	2.60	2.73	2.82	2.76	2.51	2.55
Max Tire (w/o fender)	27.5" x 2.6"									





ALEX 26

MODEL	RL	TNL	MLC	T
STEERER	28.6mm Steel			
CROWN PITCH	125 mm			
STANCHION	30mm Steel CP Finish			
CASTING	Aluminum			
DROPOUT	9mm Open Dropout			
FEATURE	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Mechanical Lock-Out	Preload Adjust
SYSTEM	Oil(R), Coil(L)		Coil	
TRAVEL (mm)	26": 80, 100 mm			
BRAKE TYPE	Disc only			
WEIGHT (kgs) (w/ 200mm steerer)	2.82	2.76	2.51	2.55
Max Tire (w/o fender)	26"X2.2"			



ANGEL 26

MODEL	RL	TNL	MLC	T
STEERER	28.6mm Steel			
CROWN PITCH	112 mm			
STANCHION	28.6mm Steel CP Finish			
CASTING	Magnesium			
DROPOUT	9mm Open Dropout			
FEATURE	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Mechanical Lock-Out	Preload Adjust
SYSTEM	Oil(R), Coil(L)		Coil	
TRAVEL (mm)	26": 60, 75 mm			
BRAKE TYPE	Disc or Disc & V-brake			
WEIGHT (kgs) (w/ 200mm steerer)	2.22	2.16	2.11	2.05
Max Tire (w/o fender)	26"X2.2"			



GILA 29/27.5/26

MODEL	RL	TNL	MLC	T
STEERER	28.6mm Steel			
CROWN PITCH	29": 130 mm/ 27.5" & 26": 125 mm			
STANCHION	28.6mm Steel CP Finish			
CASTING	Aluminum			
DROPOUT	9mm Open Dropout			
FEATURE	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Mechanical Lock-Out	Preload Adjust
SYSTEM	Oil(R), Coil(L)		Coil	
TRAVEL (mm)	29"/27.5"/26": 80, 100 mm (29" has 120mm version option)			
BRAKE TYPE	Disc Only (27.5" & 26" has Disc & V-brake option)			
WEIGHT (kgs) (w/ 200mm steerer)	29": 2.70 27.5": 2.50 26": 2.41	29": 2.64 27.5": 2.44 26": 2.35	29": 2.41 27.5": 2.19 26": 2.10	29": 2.36 27.5": 2.14 26": 2.05
Max Tire (w/o fender)	29"x2.4" or 27.5"x2.4" or 26"x2.2"			



PAVEMENT CAPA 29/27.5/26

MODEL	MLC	T
STEERER	28.6 mm Steel (26" has 25.4mm steel option)	
CROWN PITCH	29"&27.5": 125 mm/ 26": 120 mm	
STANCHION	25.4mm Steel CP Finish	
CASTING	Aluminum	
DROPOUT	9mm Open Dropout	
FEATURE	Mechanical Lock-Out	Preload Adjust
SYSTEM	Coil	
TRAVEL (mm)	29"&27.5": 60, 80 mm/ 26": 80 mm	
BRAKE TYPE	Disc or Disc & V-brake	
WEIGHT (kgs) (w/ 200mm steerer)	29": 2.07 27.5": 2.05 26": 2.03	29": 2.02 27.5": 2.00 26": 1.98
Max Tire (w/o fender)	29"x2.4" or 27.5"x2.4" or 26"x2.2"	



DIRT JUMP

The fork series for DIRT riders – Increased durability and ready for air time. Tough, short travel design combined with a top performing damping system make for forks ready to take on the toughest lines on the planet.

Rider Fred Austruy **Photographer** Jonathan Vael



SPACE 26

MODEL	Jump	Free
STEERER	28.6mm Aluminum	28.6mm Cr-mo Steel
CROWN PITCH	138 mm	
STANCHION	36mm Aluminum Hard Anodize Black	36mm Steel QPQ black
CASTING	Magnesium	
DROPOUT	20mm Bolt Axle	
FEATURE	Hydraulic Rebound adjust, Air Spring	Hydraulic Rebound adjust
SYSTEM	Oil(R), Air(L)	Oil(R), Coil(L)
TRAVEL (mm)	26": 80, 100 mm	
BRAKE TYPE	Disc Only	
WEIGHT (kgs) (w/ 200mm steerer)	2.63	2.93
Max Tire (w/o fender)	26"X2.4"	



DIRT JUMP



SLOPE 27.5/26

MODEL	
STEERER	28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)
CROWN PITCH	130 mm
STANCHION	34mm Aluminum Hard Anodize Black
CASTING	Magnesium
DROPOUT	15mm QR Axle
FEATURE	Hydraulic Compression, Rebound adjust, Air Spring
SYSTEM	OCR+(R), Air(L)
TRAVEL (mm)	27.5" / 26": 80, 100, 130 mm
BRAKE TYPE	Disc Only
WEIGHT (kgs) (w/ 200mm steerer)	27.5": 2.00 26": 1.98
Max Tire (w/o fender)	27.5"x2.4" or 26"x2.4"



DIRT 26-15/9_{mm}

MODEL	SD	RA	T	15 SD	15 RA	15 T
STEERER	28.6mm Cr-mo steel					
CROWN PITCH	130 mm					
STANCHION	32mm Steel CP Finish					
CASTING	Aluminum					
DROPOUT	9mm Open Dropout			15mm Bolt Axle		
FEATURE	Hydraulic Rebound-fixed	Hydraulic Rebound adjust	Preload Adjust	Hydraulic Rebound-fixed	Hydraulic Rebound adjust	Preload Adjust
SYSTEM	Oil(R), Coil(L)		Coil	Oil(R), Coil(L)		Coil
TRAVEL (mm)	26": 80, 100, 130 mm					
BRAKE TYPE	Disc or Disc & V-brake					
WEIGHT (kgs) (w/ 200mm steerer)	3.01	3.01	3.05	3.06	3.06	3.11
Max Tire w/o fender)	26"x2.2"					

CROSS TREKKING

Comfortable forks for touring and city bikes with travel around 50mm. Efficient suspension forks that include mounting Options that allow use of integrated lights, fenders, dynamos and even roller brake use. Carefree technical systems allow convenient daily use.





VOGUE

MODEL	Air TRL	Air
STEERER	28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)	
CROWN PITCH	120 mm	
STANCHION	28.6mm Aluminum Hard Anodize Black	
CASTING	Magnesium	
DROPOUT	9mm Open Dropout	
FEATURE	Hydraulic Rebound adjust, Remote Lock-out, Air Spring	Hydraulic Compression, Rebound adjust, Lock-out, Air Spring
SYSTEM	OCR(R), Air(L)	
TRAVEL (mm)	700C: 50, 60, 80 mm	
BRAKE TYPE	Disc or Disc & V-brake	
WEIGHT (kgs) (w/ 200mm steerer)	1.80	1.78
Max Tire (w/o fender)	700X50C	



VIV AIR

MODEL	RL	TNL
STEERER	28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)	
CROWN PITCH	120 mm	
STANCHION	28.6mm Steel QPQ black	
CASTING	Magnesium	
DROPOUT	9mm Open Dropout	
FEATURE	Hydraulic Remote Lock-out, Air Spring	Hydraulic Lock-out, Air Spring
SYSTEM	Oil(R), Air(L)	
TRAVEL (mm)	700C: 50, 60, 80 mm	
BRAKE TYPE	Disc or Disc & V-brake	
WEIGHT (kgs) (w/ 200mm steerer)	2.23	2.17
Max Tire (w/o fender)	700X50C	



VOGUE E 15/9 mm

MODEL	9 Air TRL	9 Air	15 Air TRL	15 Air
STEERER	1.5" Aluminum tapered steerer			
CROWN PITCH	130 mm			
STANCHION	30mm Aluminum Hard Anodize Black			
CASTING	Aluminum			
DROPOUT	9mm Open Dropout		15mm Bolt Axle	
FEATURE	Hydraulic Rebound adjust, Remote Lock-out, Air Spring	Hydraulic Compression, Rebound adjust, Lock-out, Air Spring	Hydraulic Rebound adjust, Remote Lock-out, Air Spring	Hydraulic Compression, Rebound adjust, Lock-out, Air Spring
SYSTEM	OCR(R), Air(L)			
TRAVEL (mm)	700C: 50, 60, 80 mm			
BRAKE TYPE	Disc Only			
WEIGHT (kgs) (w/ 200mm steerer)	2.36	2.34	2.40	2.38
Max Tire (w/o fender)	700x50C			



VIV AIR E 15/9 mm


MODEL	9 TRL	9 TNL	15 TRL	15 TNL
STEERER	28.6mm Steel (Optional 1.5" Aluminum tapered steerer)			
CROWN PITCH	130 mm			
STANCHION	30mm Steel QPQ black			
CASTING	Aluminum			
DROPOUT	9mm Open Dropout		15mm Bolt Axle	
FEATURE	Hydraulic Remote Lock-out, Air Spring	Hydraulic Lock-out, Air Spring	Hydraulic Remote Lock-out, Air Spring	Hydraulic Lock-out, Air Spring
SYSTEM	Oil(R), Air(L)			
TRAVEL (mm)	700C: 50, 60, 80 mm			
BRAKE TYPE	Disc Only			
WEIGHT (kgs) (w/ 200mm steerer)	2.80	2.74	2.84	2.78
Max Tire (w/o fender)	700x50C			





VOLANT 15/9 mm


MODEL	RL	TNL	MLC	T
STEERER	28.6mm Steel (Optional 1.5" Steel tapered steerer or 1.5" Aluminum tapered steerer)			
CROWN PITCH	130 mm			
STANCHION	30mm Steel CP Finish			
CASTING	Aluminum			
DROPOUT	15mm Bolt Axle 9mm Open Dropout			
FEATURE	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Mechanical Lock-Out	Preload Adjust
SYSTEM	Oil(R), Coil(L)		Coil	
TRAVEL (mm)	700C: 50, 60, 80 mm			
BRAKE TYPE	Disc Only			
WEIGHT (kgs) (w/ 200mm steerer)	15: 2.85 9: 2.84	15: 2.79 9: 2.78	15: 2.56 9: 2.55	15: 2.56 9: 2.55
Max Tire (w/o fender)	700x50C			



#M5GACC0921 (M5*1.0)
#M5GACC0921 for
TRELOCK and BASTA FITMENT

PLS BRACKET

FRONT LIGHT MAKER	RST BRACKET PART	AVAILABLE MODEL
BUMM	M5GACX0109-01 (using M6 Screw)	All models
AXA	M5GACC0921 (using M5 Screw)	Ecoline Pico 15/30 Echo 15/30 Compactline 20/35 Blueline 30/50
TRELOCK	M5GACC0921 (using M5 Screw)	Bike-I Veo 20/50 Bike-I Retro Bike-I Go Bike-I Prio Bike-I Airflow 70/100



#M5GACX0109-01 (M6*1.0)
#M5GACX0109-01
for BUMM FITMENT



VITA

MODEL	RL	TNL	MLC	T
STEERER	28.6mm Steel (Optional 1.5" Steel tapered steerer)			
CROWN PITCH	120 mm			
STANCHION	28.6mm Steel CP Finish			
CASTING	Magnesium			
DROPOUT	9mm Open Dropout			
FEATURE	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Mechanical Lock-Out	Preload Adjust
SYSTEM	Oil(R), Coil(L)		Coil	
TRAVEL (mm)	700C: 50, 60, 80 mm			
BRAKE TYPE	Disc or Disc & V-brake			
WEIGHT (kgs) (w/ 200mm steerer)	2.41	2.35	2.13	2.13
Max Tire (w/o fender)	700x50C			



NOVA

MODEL	RL	TNL	MLC	T
STEERER	28.6mm Steel (Optional 1.5" Steel tapered steerer)			
CROWN PITCH	112 mm			
STANCHION	28.6mm Steel CP Finish			
CASTING	Aluminum			
DROPOUT	9mm Open Dropout			
FEATURE	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Mechanical Lock-Out	Preload Adjust
SYSTEM	Oil (R), Coil (L)		Coil	
TRAVEL (mm)	700C: 50, 60 mm			
BRAKE TYPE	Disc or Disc & V-brake			
WEIGHT (kgs) (w/ 200mm steerer)	2.57	2.51	2.30	2.31
Max Tire (w/o fender)	700x50C			



NEON PLS

MODEL	RL	TNL	MLC	T
STEERER	28.6mm Steel (Optional 1.5" Steel tapered steerer)			
CROWN PITCH	112 mm			
STANCHION	28.6mm Steel CP Finish			
CASTING	Aluminum			
DROPOUT	9mm Open Dropout			
FEATURE	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Mechanical Lock-Out	Preload Adjust
SYSTEM	Oil(R), Coil(L)		Coil	
TRAVEL (mm)	700C: 50, 60 mm			
BRAKE TYPE	Disc or Disc & V-brake			
WEIGHT (kgs) (w/ 200mm steerer)	2.57	2.51	2.30	2.31
Max Tire (w/o fender)	700x50C			



NEON

MODEL	RL	TNL	MLC	T
STEERER	28.6 / 25.4mm Steel			
CROWN PITCH	112 mm			
STANCHION	25.4mm Steel CP Finish			
CASTING	Aluminum			
DROPOUT	9mm Open Dropout			
FEATURE	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Mechanical Lock-Out	Preload Adjust
SYSTEM	Oil(R), Coil(L)		Coil	
TRAVEL (mm)	700C: 50, 60 mm			
BRAKE TYPE	Disc or Disc & V-brake			
WEIGHT (kgs) (w/ 200mm steerer)	2.17	2.11	1.95	1.94
Max Tire (w/o fender)	700x50C			



VERSE

MODEL	RL	TNL	MLC	T
STEERER	28.6 / 25.4mm Steel			
CROWN PITCH	112 mm			
STANCHION	28.6mm Steel CP Finish			
CASTING	Aluminum			
DROPOUT	9mm Open Dropout			
FEATURE	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Mechanical Lock-Out	Preload Adjust
SYSTEM	Oil(R), Coil(L)		Coil	
TRAVEL (mm)	700C: 50, 60 mm			
BRAKE TYPE	V-brake only			
WEIGHT (kgs) (w/ 200mm steerer)	2.57	2.51	2.30	2.31
Max Tire (w/o fender)	700x50C			



URBAN

MODEL	RL	TNL	MLC	T
STEERER	28.6 / 25.4mm Steel			
CROWN PITCH	112 mm			
STANCHION	25.4mm Steel CP Finish			
CASTING	Aluminum			
DROPOUT	9mm Open Dropout			
FEATURE	Remote Hydraulic Lock-Out	Hydraulic Lock-Out	Mechanical Lock-Out	Preload Adjust
SYSTEM	Oil(R), Coil(L)		Coil	
TRAVEL (mm)	700C: 40 mm			
BRAKE TYPE	Roller& Disc brake only, No V-brake available			
WEIGHT (kgs) (w/ 200mm steerer)	2.13	2.07	1.86	1.87
Max Tire (w/o fender)	700x50C			



AIR/COIL

PULSE 29-15_{mm}

MODEL	Air-RL	Air-TNL	RL	TNL
STEERER	1.5" Steel tapered steerer (Optional 1.5" Aluminum tapered steerer)			
CROWN PITCH	130 mm			
STANCHION	32mm Steel QPQ Black			
CASTING	Magnesium			
DROPOUT	15mm QR Axle			
FEATURE	Hydraulic Remote Lock-out, Air Spring	Hydraulic Lock-out, Air Spring	Hydraulic Remote Lock-out	Hydraulic Lock-out,
SYSTEM	Oil(R), Air(L)		Oil(R), Coil(L)	
TRAVEL (mm)	29": 50, 60, 80, 100 mm			
BRAKE TYPE	Disc only			
WEIGHT (kgs) (w/ 200mm steerer)	2.69	2.63	2.89	2.83
Max Tire (w/o fender)	29"x2.4"			



AIR/COIL

PULSE 29

MODEL	Air-RL	Air-TNL	RL	TNL
STEERER	28.6mm Steel (Optional 1.5" Steel tapered steerer)			
CROWN PITCH	130 mm			
STANCHION	30mm Steel QPQ Black			
CASTING	Aluminum			
DROPOUT	9mm Open Dropout			
FEATURE	Hydraulic Remote Lock-out, Air Spring	Hydraulic Lock-out, Air Spring	Hydraulic Remote Lock-out	Hydraulic Lock-out
SYSTEM	Oil(R), Air(L)		Oil(R), Coil(L)	
TRAVEL (mm)	29": 50, 60 mm			
BRAKE TYPE	Disc only			
WEIGHT (kgs) (w/ 200mm steerer)	2.89	2.83	2.90	2.84
Max Tire (w/o fender)	29"x2.6"			



AIR/COIL

PULSE 27.5-15mm


MODEL	15 Air-RL		15 Air-TNL		15 RL		15 TNL	
STEERER	28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)							
CROWN PITCH	130 mm							
STANCHION	32mm Steel QPQ Black							
CASTING	Magnesium							
DROPOUT	15mm Bolt Axle							
FEATURE	Hydraulic Remote Lock-out, Air Spring		Hydraulic Lock-out, Air Spring		Hydraulic Remote Lock-out		Hydraulic Lock-out	
SYSTEM	Oil(R), Air(L)				Oil(R), Coil(L)			
TRAVEL (mm)	27.5": 60, 80, 100 mm							
BRAKE TYPE	Disc only							
WEIGHT (kgs) (w/ 200mm steerer)	2.51		2.45		2.51		2.45	
Max Tire (w/o fender)	27.5"x2.6"							



AIR/COIL

PULSE 27.5

MODEL	9 Air-RL		9 Air-TNL		9 RL		9 TNL	
STEERER	28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)							
CROWN PITCH	130 mm							
STANCHION	32mm Steel QPQ Black							
CASTING	Magnesium							
DROPOUT	9mm Open Dropout							
FEATURE	Hydraulic Remote Lock-out, Air Spring		Hydraulic Lock-out, Air Spring		Hydraulic Remote Lock-out		Hydraulic Lock-out	
SYSTEM	Oil(R), Air(L)				Oil(R), Coil(L)			
TRAVEL (mm)	27.5": 60, 80, 100 mm							
BRAKE TYPE	Disc only							
WEIGHT (kgs) (w/ 200mm steerer)	2.51		2.45		2.51		2.45	
Max Tire (w/o fender)	27.5"x2.6"							



AVALON 26-15/9_{mm}

MODEL	RL	TNL	MLC	T
STEERER	28.6mm Steel (Optional 1.5" Steel tapered steerer)			
CROWN PITCH	130 mm			
STANCHION	30mm Steel CP Finish			
CASTING	Aluminum			
DROPOUT	15mm Bolt Axle 9mm Open Dropout			
FEATURE	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Mechanical Lock-Out	Preload Adjust
SYSTEM	Oil(R), Coil(L)		Coil	
TRAVEL (mm)	26": 50, 60, 80 mm			
BRAKE TYPE	Disc only			
WEIGHT (kgs) (w/ 200mm steerer)	15: 3.01 9: 2.96	15: 2.94 9: 2.89	15: 2.71 9: 2.66	15: 2.71 9: 2.66
Max Tire (w/o fender)	26"X2.4"			



SS A8

MODEL	SS A8
STEERER	28.6 mm Aluminum (Optional 1.5" Aluminum tapered steerer) (Min. Length: 210mm)
CASTING	Aluminum
DROPOUT	9mm Open Dropout
FEATURE	Alu. Blade Changeable Spring
TRAVEL (mm)	35 mm
BRAKE TYPE	Disc or Disc + V-brake(Optional Roller Mount)
WEIGHT (kgs) (w/ 200mm steerer)	1.70
Max Tire (w/o fender)	700x50C



SS A7

MODEL	SS A7-T	SS A7
STEERER	28.6 mm Aluminum (Optional 1.5" Aluminum tapered steerer) (Min. Length: 210mm for T version & 210mm for w/o T version)	
CASTING	Aluminum	
DROPOUT	9mm Open Dropout	
FEATURES	Alu. Blade Spring Preload	Alu. Blade
TRAVEL (mm)	30 mm	35 mm
BRAKE TYPE	Disc or Disc + V-brake(Optional Roller Mount)	
WEIGHT (kgs) (w/ 200mm steerer)	1.70	
Max Tire (w/o fender)	700x50C	



SS A2

MODEL	SS-A2-100
STEERER	28.6 mm Aluminum (Min. Length: 210mm for T version & 210mm for w/o T version)
CASTING	Aluminum
DROPOUT	9mm Open Dropout
FEATURES	Alu. Blade (Straight)
TRAVEL (mm)	30 mm
BRAKE TYPE	Disc + V-brake
WEIGHT (kgs) (w/ 200mm steerer)	1.32
Max Tire (w/o fender)	20"x1.5"



SS-M7

MODEL	SS-M7 T	SS-M7
STEERER	28.6 mm Aluminum (Min. Length: 210mm for T version & 210mm for w/o T version)	
CASTING	Magnesium	
DROPOUT	9mm Open Dropout	
FEATURES	Mag. Blade Spring Preload	Mag. Blade
TRAVEL (mm)	30 mm	35 mm
BRAKE TYPE	Disc + V-brake(Optional Roller Mount)	
WEIGHT (kgs) (w/ 200mm steerer)	1.33	
Max Tire (w/o fender)	700x45C	



PILOT

MODEL	PILOT
STEERER	1.5" Aluminum tapered steerer
CASTING	Aluminum
DROPOUT	9mm Open Dropout
FEATURE	ALU. BLADE
TRAVEL (mm)	40 mm
BRAKE TYPE	Roller & Disc Brake Only
WEIGHT (kgs) (w/ 200mm steerer)	2.10
Max Tire (w/o fender)	700X47C



AM PACKAGE



AIR CARTRIDGE UPGRADE KIT

The perfect upgrade for your coil spring fork!
It covers the widest possible range of riders weight and allows for custom tuning to the riders preference. In addition, it shaves some weight compared to a standard coil spring.
Combine easy adjustability with the weight savings and this upgrade is a must have.

Fitments Available For

MODEL		
32mm Stanchion Forks	#H5GDPCDC2012-2	OMEGA 29 / 27.5, AERIAL 29 / 27.5
32mm Stanchion Forks	#H5GDPCDC2012-1	AERIAL 26
30mm Stanchion Forks	#H5GDPCDC2012-3	ALL BLAZE series



HIGH PREESURE AIR PUMP

RST's on inflation pump for suspension forks and rear shocks.
A must have for shops, mechanics, and basically all RST Air fork riders.
Dial in the perfect tune on your ride.

Fitments Available For

MODEL		
Air-Pump	#H5PFGP-2200-300	ALL RST Air forks

GREASE

Keep your suspension performing at its peak. Genuine RST grease was developed to withstand the most severe conditions. A perfectly balanced, lithium free suspension lubricant to retain that factory fresh performance of your RST fork. To be used for all suggested maintenance intervals.

Fitments Available For

MODEL		
Lubrication Kit 50g	#H5GACB182	ALL RST FORK
Lubrication Kit 5g	#H5FA1-2990-000	STEM SHOCK



SPRING SEALS

Only use genuine RST seals to keep your fork performing at its peak. Spring energized lip-seals keep the dust out and the grease in.

The dust seals need to be replaced when worn.

Fitments Available For

MODEL		
Seal for 32mm	#H5GBH8CEC1	AERIAL 110-15, ALPHA 110-15
Seal for 32mm	#H5GBHBAEC1	AERIAL 26/27.5/29/110-9, ALPHA 110-9, OMEGA 29/27.5, DIRT, PULSE 29-15
Seal for 30mm	#H5GBHCCCC1-2	F1RST 24-15, SPEX
Seal for 30mm	#H5GBH8CDC2	OMEGA 26, BLAZE 27.5/29, PULSE 27.5/29, VOLANT
Seal for 28.6mm	#H5GBH8CCC1	F1RST 24, AERIAL 24
Seal for 28.6mm	#H5GBHHCCC023	GILA 26/27.5/29, VOGUE, VIV AIR, VITA, NOVA, VERSE
Seal for 25.4 mm	#H5GBHCBC2	CAPA, NEON, URBAN



ADJUSTER (preload)

Genuine RST preload adjusters for replacement when something goes wrong. A wide range of adjustment, combined with high reliability, distinguish these adjusters.

Fitments Available For

MODEL		
Adjuster for 32mm	#H5GAEAB29-1	DIRT
Adjuster for 32mm	#H5GAE0A29-1	OMEGA 29/27.5, ALPHA series
Adjuster for 30mm	#H5GAE0A30-1	OMEGA 26
Adjuster for 30mm	#H5FVP-2162-100-1	BLAZE series, VOLANT
Adjuster for 28.6mm	#H5FNM-2163-300-1	GILA 29/27.5
Adjuster for 28.6mm	#H5FNM-2163-100-1	GILA 26, VITA, NOVA, VERSE
Adjuster for 25.4mm	#H5FNA-2162-100-1	CAPA, NEON, URBAN



RST FORK SEAL KITS

Only use genuine RST seals to keep your fork performing at its peak. Seals keep the dust out and the grease in. Sponge with oil can make fork compression smoothly. SAG ring can help to measure SAG value easily. The seal kits need to be replaced when worn.

Fitments Available For

MODEL		
Seal kits for 38mm	#H5GBHJCJC01-KT	KILLAH 29, STITCH 29
Seal kits for 36mm	#H5FX-2611-000-KT	KILLAH 27.5/26, STITCH 27.5/26, STORM, SPACE
Seal kits for 34mm	#H5GBHECKC1-KT	ROGUE, TITAN, SLOPE
Seal kits for 32mm	#H5GBH8CEC1-KT	REVOLT, REVEAL, SNYPER, RENEGADE, F1RST 26/27.5/29/110 series,



RST SPECIAL WRENCH

You have to have the right tools to do the job. Genuine RST preload adjusters have a unique shape that makes them stronger and you need the right tool to remove them for spring changes and fork services. One tool conveniently fits all forks past, present and future.

Fitments Available For

MODEL		
RST wrench For preload adjusters	#H5GAC616	OMEGA, BLAZE, GILA, CAPA, VITA, NOVA, VERSE, NEON, URBAN



CAPS

Fitments Available For

MODEL		
Cap for 32mm	#H5GAEDMG29	OMEGA 29 T / 27.5 T, ALPHA T
Cap for 30mm	#H5GAEDMG275	OMEGA 26 T, VOLANT T, ALL BLAZE T series
Cap for 28.6mm	#H5GAE8MG030	GILA 26 T, VITA T, NOVA T, VERSE T
Cap for 25.4mm	#H5FH2-2340-000	CAPA T, NEON T, URBAN T

SMART REMOTE LOCK-OUT(SRL) UPGRADE KIT

The SRL Upgrade moves your fork's compression adjustment and lock-out control to a more convenient location, on to your handlebar!
The SRL Upgrade still allows the selection of different compression settings but also a locked-out setting at your finger tips while you ride.
The SRL Upgrade Kit can be mounted on most forks with a crown mounted lock-out control.

Fitments Available For

MODEL		
SRL Upgrade Kit	H5GDPBARL2011	ALL RST fork




O-RING KIT

Only use RST genuine o-rings to for the maintenance to keep the forks performing at its peak.
Special rubber compounds keep the fork being smooth.
The O-Rings need to be replaced when worn.Please refer to the RST owners manual.

Fitments Available For

MODEL	
O-ring kit for 34mm	H5GORHGMC0-AM
O-ring kit for 32mm	H5GORHGEC0-AM

DIMENSIONS



MODEL NAME	WIDTH A	HEIGHT B	MAXIMUM ROTOR SIZE	FENDER MOUNT
KILLAH 29	<67	385	203	-
KILLAH 27.5&26	<63	365	203	-
STITCH 29	<67	385	203	-
STITCH 27.5&26	<63	365	203	-
STORM 27.5&26	<63	365	203	-
REBEL 29 / 27.5+	<76 for 27.5" + ; <63 for 29"	-	203	-
ROGUE 27.5&26	<63	365	203	-
TITAN 27.5& 26	<63	365	203	-
VIBE 27.5	<63	365	203	-
RENEGADE 26	<102	390	203	Yes
GUIDE 26	<117	410	203	Yes
GUIDE 20	<117	330	203	Yes
ROGUE 110-15	<76 for 27.5" + ; <63 for 29"	380	203	Yes
TITAN 110-15	<76 for 27.5" + ; <63 for 29"	380	203	Yes
VIBE 110-15	<76 for 27.5" + ; <63 for 29"	380	203	Yes
BLADE 110-15	<73 for 27.5" + ; <67 for 29"	392	203	Yes
FIRST 110-15 29 / 27.5+	<73 for 27.5" + ; <67 for 29"	390	180	Yes
FIRST 110-9 29 / 27.5+	<73 for 27.5" + ; <63 for 29"	378	180	Yes
FIRST 110-9 27.5 / 26	<67 for 27.5" ; <76 for 26"	365	180	Yes
AERIAL 110-15 29 / 27.5+	<73 for 27.5" + ; <67 for 29"	390	180	Yes
AERIAL 110-9 29 / 27.5+	<73 for 27.5" + ; <63 for 29"	378	180	Yes
AERIAL 110-9 27.5 / 26	<67 for 27.5" ; <76 for 26"	365	180	Yes
ALPHA 110-15 29 / 27.5+	<73 for 27.5" + ; <67 for 29"	390	180	Yes
ALPHA 110-9 29 / 27.5+	<73 for 27.5" + ; <63 for 29"	378	180	Yes
ALPHA 110-9 27.5 / 26	<67 for 27.5" ; <76 for 26"	365	180	Yes
SPACE 26	<63	365	203	-
SLOPE 27.5&26	<63	365	203	-

MODEL NAME	WIDTH A	HEIGHT B	MAXIMUM ROTOR SIZE	FENDER MOUNT
DIRT 26	<56	350	180	-
REVEAL 29&29-15	<67	385	180	Yes
REVEAL 27.5&27.5-15	<67	376	180	Yes
REVEAL 26	<63	350	180	Yes
F1RST 29&29-15	<67	385	180	Yes
F1RST 27.5&27.5-15	<67	376	180	Yes
F1RST 26	<63	350	180	Yes
AERIAL 29&29-15	<67	385	180	Yes
AERIAL 27.5&27.5-15	<67	376	180	Yes
AERIAL 26	<63	350	180	Yes
OMEAG 29&29-15	<67	385	180	Yes
OMEGA 27.5&27.5-15	<67	376	180	Yes
OMEGA 26	<63	350	180	Yes
BLAZE 29	<67	390	180	Yes
BLAZE 27.5&27.5-15	<63	370	180	Yes
ALEX 26	<56	351	180	-
GILA 29	<63	380	180	Yes
GILA 27.5	<63	365	180	Yes
GILA 26	<58	350	180	Yes
ANGEL 26	<56	355	160	-
CAPA 29	<63	380	180	Yes
CAPA 27.5	<63	365	180	Yes
CAPA 26	<56	352	160	Yes
SNYPER 24	<56	317	180	Yes
F1RST 24-15	<67	350	180	Yes
F1RST 24	<56	317	180	Yes
IGNITE 24	<56	317	180	Yes

MODEL NAME	WIDTH A	HEIGHT B	MAXIMUM ROTOR SIZE	FENDER MOUNT
AERIAL 24	<56	317	180	Yes
SPEX 20	<63	290	180	Yes
SPARK 20	<63	290	180	Yes
CAPA 24	<56	322	160	Yes
CAPA 20	<56	289	160	Yes
PORTER 20	<63	290	180	Yes
GARY 20	<67	289	160	Yes
PULSE 29-15	<63	380	180	Yes
PULSE 29	<67	390	180	Yes
PULSE 27.5&27.5-15	<63	376	180	Yes
VOGUE E	<55	381	180	Yes
VIVAir E	<55	381	180	Yes
VOGUE	<55	382	180	Yes
VIVAir	<55	382	180	Yes
VITA	<55	382	180	Yes
VOLANT	<55	381	180	Yes
AVALON 26	<63	360	180	Yes
NEON PLS	<55	381	160	Yes
NOVA	<55	381	160	Yes
VERSE	<55	377	160	Yes
NEON	<55	382	180	Yes
URBAN	<50	377	160	Yes
SS-M7 / RF-M7	<45	380	160	Yes
SS-A8	<55	382	180	Yes
SS-A7	<55	382	180	Yes
SS-A2-100	<32	265	160	Yes

Bike Category	DOWN HILL				FREE RIDE				ALL MOUNTAIN			
Model	KILLAH				STITCH				STORM	REBEL 29/27.5+		
	29 COIL	29 AIR	27.5 / 26 COIL	27.5 / 26 AIR	29 AIR	29 COIL	27.5 / 26 AIR	27.5 / 26 COIL	26/27.5	Air	Air-TRL	Air w/o Lockout
Steerer	28.6mm Aluminum				1.5" Aluminum tapered steerer		28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)		28.6mm Cr-mo steel (Optional 1.5" Aluminum tapered steerer)	1.5" Aluminum tapered steerer		
Crown	145mm-Dual		138mm-Dual		145mm		138mm		138mm	140mm		
Stanchion	38mm Aluminum		36mm Aluminum		38mm Aluminum		36mm Aluminum		36mm steel	32mm Aluminum		
	Hard Anodize Black				Hard Anodize Black				QPQ black	Hard Anodize Black		
Lower	Magnesium				Magnesium				Magnesium	Magnesium		
	20x110 mm boost Bolt Axle		20mm Bolt Axle		15x110 mm Bolt Axle (Optional 20x110 mm boost)		20mm QR Axle		20mm QR Axle	15x110 mm Bolt Axle (Optional 20x110 mm boost)		
Feature	Hydraulic Compression and Rebound adjust	Hydraulic compression and Rebound adjust, Air spring	Hydraulic Compression and Rebound adjust	Hydraulic compression and Rebound adjust, Air spring	Hydraulic compression and Rebound adjust, Air spring	Hydraulic compression and Rebound adjust	Hydraulic compression and Rebound adjust, Air spring	Hydraulic compression and Rebound adjust	Hydraulic Rebound-adjust	Hydraulic compression and Rebound adjust, Lock-out, Air Spring	Hydraulic Rebound-adjust, Remote Lock-out, Air spring	Hydraulic compression and Rebound adjust, Air spring
Damper	OCR+				OCR+				Hydraulic Cartridge	OCR+		
Spring	Coil	Air	Coil	Air	Air	Coil	Air	Coil	Coil	Air		
Travel	200mm				160, 170, 180 mm				160, 170, 180 mm	29" :80, 100, 130 mm 27.5"+: 100, 130, 140, 150 mm		
Fork offset (mm)	51mm		43mm		51mm		43mm		43mm	43mm		
Fork height (mm)	29": 610		27.5": 580 26": 565		29":605		27.5": 555 / 565 / 575 26": 540 / 550 / 560		27.5": 555 / 565 / 575 26": 540 / 550 / 560	29" : 490 / 510 / 540 27.5"+: 510 / 540 / 550 / 560		
Brake Type	Disc only				Disc only				Disc only	Disc only		
Disc Brake Mount	Post				Post				Post	Post		
Recommended Max.& Min. Rotor Size in mm	Max:203 / Min:180				Max:203 / Min:180				Max:203 / Min:180	Max:203 / Min:180		
PLS Bracket Mount	-		-		-		-		-	-		
Weight (kgs) (w/steerer at 200mm)	29":3.25	29":3.05	27.5": 3.22 26": 3.20	27.5": 3.02 26": 3.00	29":2.68	29":2.88	27.5": 2.28 26": 2.26	27.5": 2.57 26": 2.55	27.5": 3.34 26": 3.32	29" :2.25 27.5"+: 2.35	29" :2.23 27.5"+: 2.33	29" :2.23 27.5"+: 2.33
Max Tire (w/o fender)	29"x2.6"		27.5"x2.4" or 26"x2.4"		29"x2.6"		27.5"x2.4" or 26"x2.4"		27.5"x2.4" or 26"x2.4"	27.5"x3.0" or 29"x2.4"		
Origin of Production	Taiwan				Taiwan				Taiwan	Taiwan		

ALL MOUNTAIN											
ROGUE 26/27.5			TITAN 26/27.5			VIBE 27.5					
Air w/o Lockout	Air-TRL	Air	Air w/o Lockout	Air-TRL	Air	AIR-RA	AIR-RL	AIR-TNL	RA	RL	TNL
28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)			28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)			1.5" Steel tapered steerer					
130mm			130mm			130mm					
34mm Aluminum			34mm Aluminum			34mm Steel					
Hard Anodize Black			Hard Anodize Black			QPQ black					
Magnesium			Magnesium			Magnesium					
15mm QR Axle			15mm QR Axle			15mm Bolt Axle					
Hydraulic compression and Rebound adjust, Air spring	Hydraulic Rebound-adjust, Remote Lock-out, Air spring	Hydraulic compression and Rebound adjust, Lock-out, Air spring	Hydraulic compression and Rebound adjust, Air spring	Hydraulic Rebound-adjust, Remote Lock-out, Air spring	Hydraulic compression and Rebound adjust, Lock-out, Air spring	Hydraulic Rebound-adjust, Air spring	Hydraulic Remote Lock-Out, Air spring	Hydraulic Lock-Out, Air spring	Hydraulic Rebound-adjust	Hydraulic Remote Lock-Out	Hydraulic Lock-Out
OCR+			OCR			Hydraulic Cartridge					
Air			Air			Air			Coil		
140, 150, 160 mm			140, 150 mm			130, 140 mm					
43mm			43mm			43mm					
27.5": 535 / 545 / 555 26": 530 / 540 / 550			27.5": 535 / 545 26": 530 / 540			525 / 535					
Disc only			Disc only			Disc only					
Post			Post			Post					
Max:203 / Min:180			Max:203 / Min:180			Max:203 / Min:180					
-			-			-					
27.5":2.00 26":1.98	27.5":2.02 26":2.00	27.5":2.00 26":1.98	27.5":2.29 26":2.27	27.5":2.31 26":2.29*	27.5":2.29 26":2.27	2.88	2.97	2.91	3.14	3.23	3.17
27.5"x2.4" or 26"x2.4"			27.5"x2.4" or 26"x2.4"			27.5"x2.4"					
Taiwan			Taiwan			China					

Bike Category	FAT BIKE									110 PLUS					
Model	GUIDE						RENEGADE			ROGUE 110-15			TITAN 110-15		
	26 TNL	26 MLC	26 T	20 TNL	20 MLC	20 T	Air-TRL	Air	TNL	Air w/o Lockout	Air-TRL	Air	Air w/o Lockout	Air-TRL	Air
Steerer	28.6mm Steel (Optional 1.5" Steel tapered steerer)						28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)		1.5" Steel Tapered steerer	1.5" Aluminum tapered steerer			1.5" Aluminum tapered steerer		
Crown	180mm						190mm			150mm			150mm		
Stanchion	32mm Steel						32mm Aluminum		32mm Steel	34mm Aluminum			34mm Aluminum		
	CP Finish						Hard Anodize Black		CP Finish	Hard Anodize Black			Hard Anodize Black		
Lower	Aluminum						Magnesium			Magnesium			Magnesium		
	9x135mm open dropout						15x150mm QR Axle			15x110mm QR Axle			15x110mm QR Axle		
Feature	Hydraulic Lock-Out	Mechanical Lock-Out	Preload Adjust	Hydraulic Lock-Out	Mechanical Lock-Out	Preload Adjust	Hydraulic Rebound-adjust, Remote Lock-out, Air spring	Hydraulic compression and Rebound adjust, Lock-out, Air spring	Hydraulic Lock-Out	Hydraulic compression and Rebound adjust, Air spring	Hydraulic Rebound-adjust, Remote Lock-out, Air spring	Hydraulic compression and Rebound adjust, Lock-out, Air spring	Hydraulic compression and Rebound adjust, Air spring	Hydraulic Rebound-adjust, Remote Lock-out, Air spring	Hydraulic compression and Rebound adjust, Lock-out, Air spring
Damper	Hydraulic Cartridge	-	-	Hydraulic Cartridge	-	-	OCR		Hydraulic Cartridge	OCR+			OCR		
Spring	Coil						Air		Coil	Air			Air		
Travel	75, 80, 95 mm			45, 60 mm			80, 100, 120 mm			120, 130, 140, 150, 160 mm			120, 130, 140, 150 mm		
Fork offset (mm)	50mm			50mm			51mm			51mm			51mm		
Fork height (mm)	515 / 520 / 535			410 / 425			500 / 520 / 540			530 / 540 / 550 / 560 / 570			530 / 540 / 550 / 560		
Brake Type	Disc only						Disc only			Disc only			Disc only		
Disc Brake Mount	Post						Post			Post			Post		
Recommended Max.& Min. Rotor Size in mm	Max:203 / Min:160						Max:203 / Min:160			Max:203 / Min:180			Max:203 / Min:180		
PLS Bracket Mount	-						-			-			-		
Weight (kgs) (w/steerer at 200mm)	3.62	3.47	3.32	3.37	3.22	3.07	2.22	2.20	3.00	2.33	2.35	2.33	2.38	2.40	2.38
Max Tire (w/o fender)	26"x4.6			20"x4.6			26"x4.0"			27.5"x3.0" or 29"x2.4"			27.5"x3.0" or 29"x2.4"		
Origin of Production	China						Taiwan			Taiwan			Taiwan		

110 PLUS															
VIBE 110-15						BLADE 110-15				FIRST 110-15 29 / 27.5+		FIRST 110-9 29 / 27.5+		FIRST 110-9 27.5 / 26	
RA	RL	TNL	AIR-RA	AIR-RL	AIR-TNL	RL	TNL	AIR-RL	AIR-TNL	Air-TRL	Air	Air-TRL	Air	Air-TRL	Air
1.5" Steel tapered steerer						1.5" Steel tapered steerer				28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)		28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)		28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)	
150mm						140mm				140mm		140mm		140mm	
34mm Steel						34mm Steel				32mm Aluminum		32mm Aluminum		32mm Aluminum	
QPQ black						QPQ black				Hard Anodize Black		Hard Anodize Black		Hard Anodize Black	
Magnesium						Aluminum				Magnesium		Magnesium		Magnesium	
15x110mm Bolt Axle						15x110mm Bolt Axle				15x110mm Bolt Axle		9x110mm open dropout		9x110mm open dropout	
Hydraulic Rebound-adjust	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Hydraulic Rebound-adjust, Air spring	Hydraulic Remote Lock-Out, Air spring	Hydraulic Lock-Out, Air spring	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Hydraulic Remote Lock-Out, Air spring	Hydraulic Lock-Out, Air spring	Hydraulic Rebound-adjust Remote Lock-out, Air spring	Hydraulic compression and Rebound adjust, Lock-out, Air spring	Hydraulic Rebound-adjust Remote Lock-out, Air spring	Hydraulic compression and Rebound adjust, Lock-out, Air spring	Hydraulic Rebound-adjust Remote Lock-out, Air spring	Hydraulic compression and Rebound adjust, Lock-out, Air spring
Hydraulic Cartridge						Hydraulic Cartridge				OCR		OCR		OCR	
Coil			Air			Coil		Air		Air		Air		Air	
100, 120, 130, 140 mm						120, 130, 140, 150 mm				80, 100, 120 mm		80, 100, 120 mm		80, 100, 120 mm	
51mm						51mm				51mm		51mm		43mm	
510 / 530 / 540 / 550						540 / 550 / 560 / 570				500 / 520 / 540		490/510/530		27.5": 475 / 495 / 515 26": 460 / 480 / 500	
Disc only						Disc only				Disc only		Disc only		Disc only	
Post						Post				Post		Post		Post	
Max:203 / Min:180						Max:203 / Min:180				Max:180 / Min:160		Max:180 / Min:160		Max:180 / Min:160	
-						-				-		-		-	
3.47	3.56	3.50	3.27	3.36	3.30	3.06	3.00	2.86	2.80	2.12	2.10	2.02	2.00	1.85	1.83
27.5"x3.0" or 29"x2.4"						27.5"x2.8" or 29"x2.6"				27.5"x2.8" or 29"x2.6"		27.5"x2.8" or 29"x2.4"		27.5"x2.6" or 26"x3.0"	
China						China				Taiwan		Taiwan		Taiwan	

Bike Category	110 PLUS													
Model	AERIAL 110-15 29 / 27.5+			AERIAL 110-9 29 / 27.5+			AERIAL 110-9 27.5 / 26			ALPHA 110-15 29 / 27.5+				
	RL	TNL	MLC	RL	TNL	MLC	RL	TNL	MLC	RA	RL	TNL	MLC	T
Steerer	28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)			28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)			28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)			28.6mm Steel (Optional 1.5" Steel tapered steerer)				
Crown	140mm			140mm			140mm			140mm				
Stanchion	32mm Steel			32mm Steel			32mm Steel			32mm steel				
	QPQ black			QPQ black			QPQ black			CP Finish				
Lower	Magnesium			Magnesium			Magnesium			Magnesium				
	15x110mm Bolt Axle			9x110mm open dropout			9x110mm open dropout			15x110mm Bolt Axle				
Feature	Hydraulic Remote Lock-out, Air spring	Hydraulic Lock-out, Air spring	Mechanical Lock-out, Air spring	Hydraulic Remote Lock-out, Air spring	Hydraulic Lock-out, Air spring	Mechanical Lock-out, Air spring	Hydraulic Remote Lock-out, Air spring	Hydraulic Lock-out, Air spring	Mechanical Lock-out, Air spring	Hydraulic Rebound-adjust	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Mechanical Lock-out	Preload Adjust
Damper	Hydraulic Cartridge		-	Hydraulic Cartridge		-	Hydraulic Cartridge		-	Hydraulic Cartridge			-	
Spring	Air			Air			Air			Coil				
Travel	80,100,120 mm			80,100,120 mm			80,100,120 mm			80, 100, 120, 130, 135 mm				
Fork offset (mm)	51mm			51mm			43mm			51mm				
Fork height (mm)	500 / 520 / 540			490 / 510 / 530			27.5": 475/495/515 26": 460 / 480 / 500			500 / 520 / 540 / 550 / 555				
Brake Type	Disc only			Disc only			Disc only			Disc only				
Disc Brake Mount	Post			Post			Post			Post				
Recommended Max.& Min. Rotor Size in mm	Max:180 / Min:160			Max:180 / Min:160			Max:180 / Min:160			Max:180 / Min:160				
PLS Bracket Mount	-			-			-			-				
Weight (kgs) (w/steerer at 200mm)	2.61	2.55	2.32	2.51	2.45	2.22	2.34	2.28	2.05	2.62	2.75	2.64	2.44	2.44
Max Tire (w/o fender)	27.5"x2.8" or 29"x2.6"			27.5"x2.8" or 29"x2.4"			27.5"x2.6" or 26"x3.0"			27.5"x2.8" or 29"x2.6"				
Origin of Production	Taiwan			Taiwan			Taiwan			China				

110 PLUS										DIRT JUMP											
ALPHA 110-9 29 / 27.5+					ALPHA 110-9 27.5 / 26					SPACE 26		SLOPE		DIRT							
RA	RL	TNL	MLC	T	RA	RL	TNL	MLC	T	Jump	Free			SD	RA	T	15 SD	15 RA	15 T		
28.6mm Steel (Optional 1.5" Steel tapered steerer)					28.6mm Steel (Optional 1.5" Steel tapered steerer)					28.6mm Aluminum		28.6mm Cr-mo steel		28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)		28.6mm Cr-mo steel					
140mm					140mm					138mm		130mm		130mm							
32mm steel					32mm steel					36mm Aluminum		36mm steel		34mm Aluminum		32mm steel					
CP Finish					CP Finish					Hard Anodize Black		QPQ black		Hard Anodize Black		CP Finish					
Magnesium					Magnesium					Magnesium		Magnesium		Aluminum							
9x110mm open dropout					9x110mm open dropout					20mm Bolt Axle		15mm QR Axle		9mm open dropout			15mm Bolt Axle				
Hydraulic Rebound-adjust	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Mechanical Lock-out	Preload Adjust	Hydraulic Rebound-adjust	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Mechanical Lock-out	Preload Adjust	Hydraulic Rebound-adjust, Air spring	Hydraulic Rebound-adjust	Hydraulic compression and Rebound adjust, Air spring		Hydraulic Rebound-fixed	Hydraulic Rebound adjust	Preload Adjust	Hydraulic Rebound-fixed	Hydraulic Rebound adjust	Preload Adjust		
Hydraulic Cartridge			-		Hydraulic Cartridge			-		Hydraulic Cartridge		OCR+		Hydraulic Cartridge		-		Hydraulic Cartridge		-	
Coil					Coil					Air		Coil		Air		Coil					
80, 100, 120, 130, 140 mm					80, 100, 120, 130, 140 mm					80, 100 mm		80, 100, 130 mm		80, 100, 130 mm							
51mm					43mm					43mm		43mm		38mm							
490 / 510 / 530 / 540 / 550					27.5": 475 / 495 / 515 / 525 / 535 26": 460 / 480 / 500 / 510 / 520					465 / 485		27.5": 475 / 495 / 525 26": 470 / 490 / 520		460 / 480 / 510							
Disc only					Disc only					Disc only		Disc only		Disc or D+V-brake							
Post					Post					Post		Post		Post							
Max:180 / Min:160					Max:180 / Min:160					Max:203 / Min:180		Max:203 / Min:180		Max:180 / Min:160							
-					-					-		-		-							
2.54	2.65	2.57	2.34	2.34	2.37	2.46	2.4	2.17	2.17	2.63	2.93	27.5": 2.00 26": 1.98"		3.01	3.01	3.05	3.06	3.06	3.11		
27.5"x2.8" or 29"x2.4"					27.5"x2.6" or 26"x3.0"					26"x2.4"		27.5"x2.4" or 26"x2.4"		26"x2.2"							
China					China					Taiwan		Taiwan		China							

Bike Category	XC 29er				XC 27.5				XC 26		XC 29er			
Model	REVEAL				REVEAL				REVEAL		F1RST			
	29-15 TRL	29-15	29 TRL	29	27.5-15 TRL	27.5-15	27.5 TRL	27.5	26 TRL	26	29-15 TRL	29-15	29 TRL	29
Steerer	28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)				28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)				28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)		28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)			
Crown	130mm				130mm				130mm		130mm			
Stanchion	32mm Aluminum				32mm Aluminum				32mm Aluminum		32mm Aluminum			
	Hard Anodize Black				Hard Anodize Black				Hard Anodize Black		Hard Anodize Black			
Lower	Magnesium				Magnesium				Magnesium		Magnesium			
	15mm QR Axle		9mm open dropout		15mm QR Axle		9mm open dropout		9mm open dropout		15mm QR Axle		9mm open dropout	
Feature	Hydraulic Rebound-adjust, Remote Lock-out, Air spring	Hydraulic compression and Rebound adjust, Lock-out, Air spring	Hydraulic Rebound-adjust, Remote Lock-out, Air spring	Hydraulic compression and Rebound adjust, Lock-out, Air spring	Hydraulic Rebound-adjust, Remote Lock-out, Air spring	Hydraulic compression and Rebound adjust, Lock-out, Air spring	Hydraulic Rebound-adjust, Remote Lock-out, Air spring	Hydraulic compression and Rebound adjust, Lock-out, Air spring	Hydraulic Rebound-adjust, Remote Lock-out, Air spring	Hydraulic compression and Rebound adjust, Lock-out, Air spring	Hydraulic Rebound-adjust, Remote Lock-out, Air spring	Hydraulic compression and Rebound adjust, Lock-out, Air spring	Hydraulic Rebound-adjust, Remote Lock-out, Air spring	Hydraulic compression and Rebound adjust, Lock-out, Air spring
Damper	OCR+				OCR+				OCR+		OCR			
Spring	Air				Air				Air		Air			
Travel	80, 100, 120 mm				80, 100, 120 mm				80, 100, 120 mm		80, 100, 120 mm			
Fork offset (mm)	51mm				43mm				38mm		51mm			
Fork height (mm)	495 / 515 / 535				485 / 505 / 525				460 / 480 / 500		495 / 515 / 535			
Brake Type	Disc only				Disc only				Disc or D+V-brake		Disc only			
Disc Brake Mount	Post				Post				Post		Post			
Recommended Max. & Min. Rotor Size in mm	Max:180 / Min:160				Max:180 / Min:160				Max:180 / Min:160		Max:180 / Min:160			
PLS Bracket Mount	-				-				-		-			
Weight (kgs) (w/steerer at 200mm)	1.82	1.80	1.80	1.61	1.78	1.76	1.73	1.71	1.53	1.51	2.15	2.13	1.96	1.94
Max Tire (w/o fender)	29"x2.6"				27.5"x2.6"				26"x2.4"		29"x2.6"			
Origin of Production	Taiwan				Taiwan				Taiwan		Taiwan			

XC 27.5				XC 26		XC 29er		XC 27.5		XC 26	
FIRST				FIRST		AERIAL Rebound 29		AERIAL Rebound 27.5		AERIAL Rebound 26	
27.5-15 TRL	27.5-15	27.5 TRL	27.5	26 TRL	26	RL-R	TNL-R	RL-R	TNL-R	RL-R	TNL-R
28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)				28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)		28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)		28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)		28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)	
130mm				130mm		130mm		130mm		130mm	
32mm Aluminum				32mm Aluminum		32mm Steel		32mm Steel		32mm Steel	
Hard Anodize Black				Hard Anodize Black		QPQ black		QPQ black		QPQ black	
Magnesium				Magnesium		Magnesium		Magnesium		Magnesium	
15mm QR Axle		9mm open dropout		9mm open dropout		9mm open dropout		9mm open dropout		9mm open dropout	
Hydraulic Rebound adjust, Remote Lock-out, Air spring	Hydraulic compression and Rebound adjust, Lock-out, Air spring	Hydraulic Rebound-adjust, Remote Lock-out, Air spring	Hydraulic compression and Rebound adjust, Lock-out, Air spring	Hydraulic Rebound-adjust, Remote Lock-out, Air spring	Hydraulic compression and Rebound adjust, Lock-out, Air spring	Hydraulic Rebound-adjust, Remote Lock-out, Air spring	Hydraulic Rebound-adjust, Lock-out, Air spring	Hydraulic Rebound-adjust, Remote Lock-out, Air spring	Hydraulic Rebound-adjust, Lock-out, Air spring	Hydraulic Rebound-adjust, Remote Lock-out, Air spring	Hydraulic Rebound-adjust, Lock-out, Air spring
OCR				OCR		Hydraulic Cartridge		Hydraulic Cartridge		Hydraulic Cartridge	
Air				Air		Air		Air		Air	
80,100, 120 mm				80, 100, 120 mm		80,100,120 mm		80, 100,120 mm		80,100,120 mm	
43mm				38mm		51mm		43mm		38mm	
485 / 505 / 525				460 / 480 / 500		495 / 515 / 535		485 / 505 / 525		460 / 480 / 500	
Disc only				Disc or D+V-brake		Disc only		Disc only		Disc or D+V-brake	
Post				Post		Post		Post		Post	
Max:180 / Min:160				Max:180 / Min:160		Max:180 / Min:160		Max:180 / Min:160		Max:180 / Min:160	
-				-		-		-		-	
2.10	2.08	2.05	2.03	1.82	1.80	2.40	2.34	2.42	2.36	2.37	2.31
27.5"x2.6"				26"x2.4"		29"x2.6"		27.5"x2.6"		26"x2.4"	
Taiwan				Taiwan		Taiwan		Taiwan		Taiwan	

Bike Category	XC 29er						XC 27.5						XC 26		
Model	AERIAL						AERIAL						AERIAL		
	29-15 RL	29-15 TNL	29-15 MLC	29 RL	29 TNL	29 MLC	27.5-15 RL	27.5-15 TNL	27.5-15 MLC	27.5 RL	27.5 TNL	27.5 MLC	26 RL	26 TNL	26 MLC
Steerer	28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)						28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)						28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)		
Crown	130mm						130mm						130mm		
Stanchion	32mm Steel						32mm Steel						32mm Steel		
	QPQ black						QPQ black						QPQ black		
Lower	Magnesium						Magnesium						Magnesium		
	15mm Bolt Axle			9mm open dropout			15mm Bolt Axle			9mm open dropout			9mm open dropout		
Feature	Hydraulic Remote Lock-out, Air spring	Hydraulic Lock-out, Air spring	Mechanical Lock-out, Air spring	Hydraulic Remote Lock-out, Air spring	Hydraulic Lock-out, Air spring	Mechanical Lock-out, Air spring	Hydraulic Remote Lock-out, Air spring	Hydraulic Lock-out, Air spring	Mechanical Lock-out, Air spring	Hydraulic Remote Lock-out, Air spring	Hydraulic Lock-out, Air spring	Mechanical Lock-out, Air spring	Hydraulic Remote Lock-out, Air spring	Hydraulic Lock-out, Air spring	Mechanical Lock-out, Air spring
Damper	Hydraulic Cartridge		-	Hydraulic Cartridge		-	Hydraulic Cartridge		-	Hydraulic Cartridge		-	Hydraulic Cartridge		
Spring	Air						Air						Air		
Travel	80,100,120 mm						80, 100,120 mm						80,100,120 mm		
Fork offset (mm)	51mm						43mm						38mm		
Fork height (mm)	495 / 515 / 535						485 / 505 / 525						460 / 480 / 500		
Brake Type	Disc only						Disc only						Disc or D+V-brake		
Disc Brake Mount	Post						Post						Post		
Recommended Max.& Min. Rotor Size in mm	Max:180 / Min:160						Max:180 / Min:160						Max:180 / Min:160		
PLS Bracket Mount	-						-						-		
Weight (kgs) (w/steerer at 200mm)	2.53	2.47	2.27	2.34	2.28	2.05	2.41	2.35	2.15	2.36	2.30	2.10	2.31	2.25	2.02
Max Tire (w/o fender)	29"x2.6"						27.5"x2.6"						26"x2.4"		
Origin of Production	Taiwan						Taiwan						Taiwan		

XC 29er										XC 27.5									
OMEGA										OMEGA									
29-15 RA	29-15 RL	29-15 TNL	29-15 MLC	29-15 T	29 RA	29 RL	29 TNL	29 MLC	29 T	27.5-15 RA	27.5-15 RL	27.5-15 TNL	27.5-15 MLC	27.5-15 T	27.5 RA	27.5 RL	27.5 TNL	27.5 MLC	27.5 T
28.6mm Steel (Optional 1.5" Steel tapered steerer)										28.6mm Steel (Optional 1.5" Steel tapered steerer)									
130mm										130mm									
32 steel										32 steel									
CP Finish										CP Finish									
Magnesium										Magnesium									
15mm Bolt Axle					9mm open dropout					15mm Bolt Axle					9mm open dropout				
Hydraulic Rebound-adjust	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Mechanical Lock-out	Preload Adjust	Hydraulic Rebound-adjust	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Mechanical Lock-out	Preload Adjust	Hydraulic Rebound-adjust	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Mechanical Lock-out	Preload Adjust	Hydraulic Rebound-adjust	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Mechanical Lock-out	Preload Adjust
Hydraulic Cartridge			-		Hydraulic Cartridge			-		Hydraulic Cartridge			-		Hydraulic Cartridge			-	
Coil										Coil									
80, 100, 120 mm										80, 100, 120 mm									
51mm										43mm									
495 / 515 / 535										495/505/525									
Disc only										Disc only									
Post										Post									
Max:180 / Min:160										Max:180 / Min:160									
-										-									
2.49	2.60	2.52	2.29	2.29	2.44	2.55	2.47	2.24	2.24	2.32	2.41	2.35	2.12	2.12	2.27	2.36	2.30	2.07	2.07
29"x2.6"										27.5"x2.6"									
China										China									

Bike Category	XC 26					XC 29er				
Model	OMEGA					BLAZE				
	26 RA	26 RL	26 TNL	26 MLC	26 T	29 RA	29 RL	29 TNL	29 MLC	29 T
Steerer	28.6mm Steel (Optional 1.5" Steel tapered steerer)					28.6mm Steel (Optional 1.5" Steel tapered steerer)				
Crown	130mm					130mm				
Stanchion	32mm Steel					30mm steel				
	CP Finish					CP Finish				
Lower	Magnesium					Aluminum				
	9mm open dropout					9mm open dropout				
Feature	Hydraulic Rebound-adjust	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Mechanical Lock-out	Preload Adjust	Hydraulic Rebound-adjust	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Mechanical Lock-out	Preload Adjust
Damper	Hydraulic Cartridge			-		Hydraulic Cartridge			-	
Spring	Coil					Coil				
Travel	80, 100, 120 mm					80, 100, 120 mm				
Fork offset (mm)	38mm					51mm				
Fork height (mm)	460 / 480 / 500					500 / 520 / 540				
Brake Type	Disc or D+V-brake					Disc Only				
Disc Brake Mount	Post					Post				
Recommended Max.& Min. Rotor Size in mm	Max:180 / Min:160					Max:180 / Min:160				
PLS Bracket Mount	-					-				
Weight (kgs) (w/steerer at 200mm)	2.34	2.44	2.37	2.11	2.11	2.81	2.90	2.84	2.61	2.61
Max Tire (w/o fender)	26"x2.4"					29"x2.6"				
Origin of Production	China					China				

XC 27.5"										XC 26"				XC/Sport 29er			
BLAZE										ALEX				GILA			
27.5-15 RA	27.5-15 RL	27.5-15 TNL	27.5-15 MLC	27.5-15 T	27.5 RA	27.5 RL	27.5 TNL	27.5 MLC	27.5 T	26 RL	26 TNL	26 MLC	26 T	29 RL	29TNL	29 MLC	29 T
28.6mm Steel										28.6mm Steel				28.6mm Steel			
130mm										125mm				130mm			
30mm steel										30mm Steel				28.6mm steel			
CP Finish										CP Finish				CP Finish			
Aluminum										Aluminum				Aluminum			
15mm Bolt Axle					9mm open dropout					9mm open dropout				9mm open dropout			
Hydraulic Rebound-adjust	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Mechanical Lock-Out	Preload Adjust	Hydraulic Rebound-adjust	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Mechanical Lock-Out	Preload Adjust	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Mechanical Lock-Out	Preload Adjust	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Mechanical Lock-Out	Preload Adjust
Hydraulic Cartridge			-		Hydraulic Cartridge			-		Hydraulic Cartridge		-		Hydraulic Cartridge		-	
Coil										Coil				Coil			
80, 100, 120 mm										80, 100 mm				80, 100, 120 mm			
44mm										38mm				51mm			
475 / 495 / 515										460 / 480				490 / 510 / 530			
Disc only										Disc only				Disc only			
Post										Post				Post			
Max:180 / Min:160										Max:180 / Min:160				Max:180 / Min:160			
-										-				-			
2.78	2.87	2.81	2.56	2.60	2.73	2.82	2.76	2.51	2.55	2.82	2.76	2.51	2.55	2.70	2.64	2.41	2.41
27.5"x2.6"										26"x2.2"				29"x2.4"			
China										China				China			

Bike Category	XC/Sport 27.5"				XC/Sport 26"				XC/Sport 26"				Pavement					
Model	GILA 27.5				GILA 26				ANGEL				CAPA					
	27.5 RL	27.5 TNL	27.5 MLC	27.5 T	26 RL	26 TNL	26 MLC	26 T	26 RL	26 TNL	26 MLC	26 T	29 MLC	29 T	27.5 MLC	27.5 T	26 MLC	26 T
Steerer	28.6mm Steel				28.6mm Steel				28.6mm Steel				28.6mm Steel		28.6mm Steel		28.6/25.4mm Steel	
Crown	125mm				125mm				112mm				125mm		125mm		120mm	
Stanchion	28.6mm steel				28.6mm steel				28.6mm Steel				25.4mm steel		25.4mm steel		25.4mm steel	
	CP Finish				CP Finish				CP Finish				CP Finish		CP Finish		CP Finish	
Lower	Aluminum				Aluminum				Magnesium				Aluminum		Aluminum		Aluminum	
	9mm open dropout				9mm open dropout				9mm open dropout				9mm open dropout		9mm open dropout		9mm open dropout	
Feature	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Mechanical Lock-Out	Preload Adjust	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Mechanical Lock-Out	Preload Adjust	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Mechanical Lock-Out	Preload Adjust	Mechanical Lock-Out	Preload Adjust	Mechanical Lock-Out	Preload Adjust	Mechanical Lock-Out	Preload Adjust
Damper	Hydraulic Cartridge		-		Hydraulic Cartridge		-		Hydraulic Cartridge		-		-		-		-	
Spring	Coil				Coil				Coil				Coil		Coil		Coil	
Travel	80, 100 mm				80, 100 mm				60, 75 mm				60, 80 mm		60, 80 mm		80mm	
Fork offset (mm)	43mm				38mm				43mm				51mm		43mm		38mm	
Fork height (mm)	475 / 495				460 / 480				450 / 460				470 / 490		455 / 475		460	
Brake Type	Disc or D+V-brake				Disc or D+V-brake				Disc or D+V-brake				Disc or D+V brake		Disc or D+V brake		Disc or D+V brake	
Disc Brake Mount	Post				Post				IS				Post		Post		IS	
Recommended Max.& Min. Rotor Size in mm	Max:180 / Min:160				Max:180 / Min:160				Max:160 / Min:140				Max:180 / Min:160		Max:180 / Min:160		Max:160 / Min:140	
PLS Bracket Mount	-				-				-				-		-		-	
Weight (kgs) (w/steerer at 200mm)	2.50	2.44	2.19	2.14	2.41	2.35	2.10	2.05	2.22	2.16	2.11	2.05	2.28	2.23	2.15	2.10	2.03	1.98
Max Tire (w/o fender)	27.5"x2.4"				26"x2.2"				26"x2.2"				29"x2.4"		27.5"x2.4"		26"x2.2"	
Origin of Production	China				China				China				China		China		China	

JUNIOR														
SNYPER		IGNITE			SPEX				SPARK					
24 TRL	24	24 RL	24 TNL	24 MLC	20 TRL	20 AIR	20-15 TRL	20-15 AIR	20 RL	20 TNL	20 MLC	20-15 RL	20-15 TNL	20-15 MLC
28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)		28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)			28.6mm Aluminum				28.6mm Aluminum					
130mm		130mm			125mm				125mm					
32mm Aluminum		32mm Steel			30mm Aluminum				30mm Aluminum					
Hard Anodize Black		QPQ black			Hard Anodize Black				Hard Anodize Black					
Magnesium		Magnesium			Magnesium				Magnesium					
9mm open dropout		9mm open dropout			9mm open dropout		15mm Bolt Axle		9mm open dropout			15mm Bolt Axle		
Hydraulic Rebound-adjust Remote Lock-out, Air spring	Hydraulic compression and Rebound adjust, Lock-out, Air spring	Hydraulic Remote Lock-out, Air spring	Hydraulic Lock-out, Air spring	Mechanical Lock-out, Air spring	Hydraulic Rebound-adjust, Remote Lock-out, Air spring	Hydraulic compression and Rebound adjust,Lock-out, Air spring	Hydraulic Rebound-adjust, Remote Lock-out, Air spring	Hydraulic compression and Rebound adjust, Lock-out, Air spring	Hydraulic Remote Lock-out, Air spring	Hydraulic Lock-out, Air spring	Mechanical Lock-out, Air spring	Hydraulic Remote Lock-out, Air spring	Hydraulic Lock-out, Air spring	Mechanical Lock-out, Air spring
OCR		Hydraulic Cartridge		-	OCR				Hydraulic Cartridge		-	Hydraulic Cartridge		-
Air		Air			Air				Air					
60, 70, 80, 100, 120 mm		80, 100, 120 mm			60, 80, 100 mm				60, 80, 100 mm					
38mm		38mm			38mm				38mm					
410 / 420 / 430 / 450 / 470		430 / 450 / 470			383 / 403/ 423				383 / 403 / 423					
Disc only		Disc only			Disc or D+V brake				Disc or D+V brake					
Post		Post			Post				Post					
Max:180 / Min:160		Max:180 / Min:160			Max:180 / Min:160				Max:180 / Min:160					
-		-			-				-					
1.87	1.85	2.31	2.25	2.05	1.70	1.65	1.80	1.75	2.31	2.25	2.05	2.26	2.20	2.00
24"x2.2"		24"x2.2"			20"x2.4"				20"x2.4"					
Taiwan		Taiwan			Taiwan				Taiwan					

Bike Category	JUNIOR								CARGO			E-Bike					
Model	F1RST				AERIAL			CAPA		GARY		PORTER		PULSE AIR			
	24-15 TRL	24-15	24 TRL	24	24 RL	24 TNL	24 MLC	24 MLC	24T, 20T	T	T	15T	29-15 RL	29-15 TNL	29 RL	29 TNL	
Steerer	28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)		28.6mm Aluminum		28.6mm Aluminum			28.6/25.4mm Steel		28.6mm Steel		28.6mm Cr-mo steel		1.5" Steel tapered steerer (Optional 1.5" Aluminum tapered steerer)		28.6mm Steel (Optional 1.5" Steel tapered steerer)	
Crown	130mm		125mm		125mm			120mm		125mm		125mm		130mm		130mm	
Stanchion	30mm Aluminum		28.6mm Aluminum		28.6mm steel			25.4 steel		28.6mm steel		30mm steel		32mm steel		30mm steel	
	Hard Anodize Black		Hard Anodize Black		QPQ black			CP Finish		CP Finish		CP Finish		QPQ black		QPQ black	
Lower	Magnesium		Magnesium		Magnesium			Aluminum		Aluminum		Magnesium		Magnesium		Aluminum	
	15mm QR Axle		9mm open dropout		9mm open dropout			9mm open dropout		9mm open dropout		9mm open dropout	15mm Bolt Axle	15mm QR Axle		9mm open dropout	
Feature	Hydraulic Rebound-adjust, Remote Lock-out, Air spring	Hydraulic compression and Rebound adjust, Lock-out, Air spring	Hydraulic Rebound-adjust, Remote Lock-out, Air spring	Hydraulic compression and Rebound adjust, Lock-out, Air spring	Hydraulic Remote Lock-out, Air spring	Hydraulic Lock-out, Air spring	Mechanical Lock-out, Air spring	Mechanical Lock-Out	Preload Adjust	Preload Adjust		Preload Adjust		Hydraulic Remote Lock-out, Air spring	Hydraulic Lock-out, Air spring	Hydraulic Remote Lock-out, Air spring	Hydraulic Lock-out, Air spring
Damper	OCR		OCR		Hydraulic Cartridge		-	-	-	-		-		Hydraulic Cartridge		Hydraulic Cartridge	
Spring	Air		Air		Air			Coil		Coil		Coil		Air		Air	
Travel	80, 100, 120 mm		60mm		60mm			24": 50 mm	24"/20": 50 mm	50mm		60, 80 mm		50, 60, 80, 100 mm		50, 60 mm	
Fork offset (mm)	38mm		38mm		38mm			38mm		43mm		38mm		51mm		51mm	
Fork height (mm)	460 / 480 / 500		410		410			24": 399	24/20": 393 / 373	373		383 / 403		460 / 470 / 490 / 510		470 / 480	
Brake Type	Disc Only		Disc only		Disc only			Disc or D+V-brake		Disc & V-brake		Disc or D+V-brake		Disc only		Disc only	
Disc Brake Mount	Post		Post		Post			IS		IS		Post		Post		Post	
Recommended Max.& Min. Rotor Size in mm	Max:180 / Min:160		Max:180 / Min:160		Max:180 / Min:160			Max:160 / Min:140		Max:160 / Min:140		Max:180 / Min:160		Max:180 / Min:160		Max:180 / Min:160	
PLS Bracket Mount	-		-		-			-		-		-		-		-	
Weight (kgs) (w/steerer at 200mm)	1.92	1.90	1.62	1.60	1.99	1.93	1.73	1.93	1.84/1.75	2.17		2.09	2.14	2.69	2.63	2.89	2.83
Max Tire (w/o fender)	24"x2.6"		24"x2.2"		24"x2.2"			24"x2.2"		20"x2.6"		20"x2.4"		29"x2.4"		29"x2.6"	
Origin of Production	Taiwan		Taiwan		Taiwan			China		China		China		Taiwan		Taiwan	

E-Bike										CROSS TREKKING							
PULSE AIR				PULSE COIL						VOGUE E				VIVAir E			
27.5-15 RL	27.5-15 TNL	27.5 RL	27.5 TNL	29 RL	29 TNL	27.5-15 RL	27.5-15 TNL	27.5 RL	27.5 TNL	Air TRL	Air	15 Air TRL	15 Air	RL	TNL	15 RL	15 TNL
28.6mm Steel (Optional 1.5" Steel tapered steerer)				28.6mm Steel (Optional 1.5" Steel tapered steerer)		28.6mm Steel (Optional 1.5" Steel tapered steerer)				1.5" Aluminum tapered steerer				28.6mm Steel (Optional 1.5" Aluminum tapered steerer)			
130mm				130mm		130mm				130mm				130mm			
32mm Steel				30mm Steel		32mm Steel				30mm Aluminum				30mm steel			
QPQ black				QPQ black		QPQ black				Hard Anodize Black				QPQ black			
Magnesium				Aluminum		Magnesium				Aluminum				Aluminum			
15mm Bolt Axle		9mm open dropout		9mm open dropout		15mm Bolt Axle		9mm open dropout		9mm open dropout		15mm Bolt Axle		9mm open dropout		15mm Bolt Axle	
Hydraulic Remote Lock-out, Air spring	Hydraulic Lock-out, Air spring	Hydraulic Remote Lock-out, Air spring	Hydraulic Lock-out, Air spring	Hydraulic Remote Lock-out	Hydraulic Lock-out	Hydraulic Remote Lock-out	Hydraulic Lock-out	Hydraulic Rebound Lock-out	Hydraulic Lock-out	Hydraulic Rebound-adjust, Remote Lock-out, Air spring	Hydraulic compression and Rebound adjust, Lock-out, Air spring	Hydraulic Rebound-adjust, Remote Lock-out, Air spring	Hydraulic compression and Rebound adjust, Lock-out, Air spring	Hydraulic Remote Lock-out, Air spring	Hydraulic Lock-out, Air spring	Hydraulic Remote Lock-out, Air spring	Hydraulic Lock-out, Air spring
Hydraulic Cartridge				Hydraulic Cartridge		Hydraulic Cartridge				OCR				Hydraulic Cartridge			
Air				Coil		Coil				Air				Air			
60, 80, 100 mm				50mm		60, 80, 100 mm				50, 60, 80 mm				50, 60, 80 mm			
43mm				51mm		43mm				44mm				44mm			
465 / 485 / 505				470		465 / 485 / 505				460 / 470 / 490				460 / 470 / 490			
Disc only				Disc only		Disc only				Disc only				Disc only			
Post				Post		Post				Post				Post			
Max:180 / Min:160				Max:180 / Min:160		Max:180 / Min:160				Max:180 / Min:160				Max:180 / Min:160			
-		-		-		-				yes				yes			
2.38	2.32	2.36	2.30	2.90	2.54	2.54	2.75	2.82	2.76	2.25	2.23	2.30	2.28	2.80	2.74	2.85	2.79
27.5"x2.6"				29"x2.6"		27.5"x2.6"				700x50C				700x50C			
Taiwan				Taiwan						Taiwan				Taiwan			

Bike Category	CROSS TREKKING															
Model	VOGUE		VIVAir		VITA				AVALON							
	Air TRL	Air	RL	TNL	RL	TNL	MLC	T	RL	TNL	MLC	T	15 RL	15 TNL	15 MLC	15 T
Steerer	28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)		28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer)		28.6mm Steel (Optional 1.5" Steel tapered steerer)				28.6mm Steel (Optional 1.5" Steel tapered steerer)							
Crown	120 mm		120mm		120mm				130mm							
Stanchion	28.6mm Aluminum		28.6mm steel		28.6mm steel				30mm steel							
	Hard Anodize Black		QPQ black		CP Finish				CP Finish							
Lower	Magnesium		Magnesium		Magnesium				Aluminum							
	9mm open dropout		9mm open dropout		9mm open dropout				9mm open dropout				15mm Bolt Axle			
Feature	Hydraulic Rebound-adjust, Remote Lock-out, Air spring	Hydraulic compression and Rebound adjust, Lock-out, Air spring	Hydraulic Remote Lock-out, Air spring	Hydraulic Lock-out, Air spring	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Mechanical Lock-Out	Preload Adjust	Hydraulic Remote Lock-Out	Hydraulic Lock-out,	Mechanical Lock-Out	Preload Adjust	Hydraulic Remote Lock-Out	Hydraulic Lock-out,	Mechanical Lock-Out	Preload Adjust
Damper	OCR		Hydraulic Cartridge		Hydraulic Cartridge		-		Hydraulic Cartridge		-		Hydraulic Cartridge		-	
Spring	Air		Air		Coil				Coil							
Travel	50, 60, 80 mm		50, 60, 80 mm		50, 60, 80 mm				50, 60, 80 mm							
Fork offset (mm)	44mm		44mm		44mm				44mm							
Fork height (mm)	460 / 470 / 490		460 / 470 / 490		460 / 470 / 490				440 / 450 / 470							
Brake Type	Disc or D+V-brake		Disc or D+V-brake		Disc or D+V-brake				Disc only							
Disc Brake Mount	Post		Post		Post				Post							
Recommended Max.& Min. Rotor Size in mm	Max:180 / Min:160		Max:180 / Min:160		Max:180 / Min:160				Max:180 / Min:160							
PLS Bracket Mount	yes		yes		yes				yes							
Weight (kgs) (w/steerer at 200mm)	1.80	1.78	2.23	2.17	2.41	2.35	2.13	2.13	2.95	2.89	2.66	2.66	2.96	2.90	2.67	2.67
Max Tire (w/o fender)	700x50C		700x50C		700x50C				26"x2.4"							
Origin of Production	Taiwan		Taiwan		China				China							


CROSS TREKKING															
VOLANT								NOVA				NEON PLS			
RL	TNL	MLC	T	15 RL	15 TNL	15 MLC	15 T	RL	TNL	MLC	T	RL	TNL	MLC	T
28.6mm Steel (Optional 1.5" Steel tapered steerer)								28.6mm Steel				28.6mm Steel			
130mm								112mm				112mm			
30mm steel								28.6mm steel				28.6mm steel			
CP Finish								CP Finish				CP Finish			
Aluminum								Aluminum				Aluminum			
9mm open dropout				15mm Bolt Axle				9mm open dropout				9mm open dropout			
Hydraulic Remote Lock-Out	Hydraulic Lock-out,	Mechanical Lock-Out	Preload Adjust	Hydraulic Remote Lock-Out	Hydraulic Lock-out	Mechanical Lock-Out	Preload Adjust	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Mechanical Lock-Out	Preload Adjust	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Mechanical Lock-Out	Preload Adjust
Hydraulic Cartridge		-		Hydraulic Cartridge		-		Hydraulic Cartridge		-		Hydraulic Cartridge		-	
Coil								Coil				Coil			
50, 60, 80 mm								50, 60 mm				50, 60 mm			
44mm								44mm				44mm			
460 / 470 / 490								466 / 476				466 / 476			
Disc or D+V-brake								Disc or D+V-brake				Disc or D+V-brake			
Post								IS				IS			
Max:180 / Min:160								Max:160 / Min:140				Max:160 / Min:140			
yes								yes				yes			
2.84	2.78	2.55	2.55	2.85	2.79	2.56	2.56	2.62	2.56	2.35	2.36	2.62	2.56	2.35	2.36
700x50C								700x50C				700x50C			
China								China				China			

Bike Category	CROSS TREKKING											
Model	VERSE				NEON				URBAN			
	RL	TNL	MLC	T	RL	TNL	ML	T	RL	TNL	MLC	T
Steerer	28.6/25.4mm Steel				28.6/25.4mm Steel				28.6/25.4mm Steel			
Crown	112mm				112mm				112mm			
Stanchion	28.6mm steel				25.4mm steel				25.4mm steel			
	CP Finish				CP Finish				CP Finish			
Lower	Aluminum				Aluminum				Aluminum			
	9mm open dropout				9mm open dropout				9mm open dropout			
Feature	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Mechanical Lock-Out	Preload Adjust	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Mechanical Lock-Out	Preload Adjust	Hydraulic Remote Lock-Out	Hydraulic Lock-Out	Mechanical Lock-Out	Preload Adjust
Damper	Hydraulic Cartridge		-		Hydraulic Cartridge		-		Hydraulic Cartridge		-	
Spring	Coil				Coil				Coil			
Travel	40, 50 mm				50, 60 mm				40mm			
Fork offset (mm)	44mm				44mm				44mm			
Fork height (mm)	450 / 460				460 / 470				450			
Brake Type	V-brake only				Disc or Disc+V-brake				Roller& Disc brake only, no V-brake available			
Disc Brake Mount	N/A				POST				IS			
Recommended Max.& Min. Rotor Size in mm	N/A				Max:180 / Min:160				Max:160 / Min:140			
PLS Bracket Mount	no				yes				yes			
Weight (kgs) (w/steerer at 200mm)	2.57	2.51	2.30	2.31	2.17	2.11	1.95	1.94	2.13	2.07	1.86	1.87
Max Tire (w/o fender)	700x50C				700x50C				700x50C			
Origin of Production	China				China				China			

SINGLE SHOCK							
Model	SS-M7-T	SS-M7	SS-A8	SS-A7-T	SS-A7	SS-A2-100	PILOT
Steerer	28.6mm Aluminum (210mm length min.)	28.6mm Aluminum (210mm length min.)	28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer) (210mm length min.)	28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer) (210mm length min.)	28.6mm Aluminum (Optional 1.5" Aluminum tapered steerer) (210mm length min.)	28.6mm Aluminum (210mm length min.)	1.5" Aluminum tapered steerer (210mm length min.)
Lower	Magnesium	Magnesium	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum
	9mm open dropout	9mm open dropout	9mm open dropout	9mm open dropout	9mm open dropout	9mm open dropout	9mm open dropout
Feature	Mag. blade Spring preload	Mag. blade	Alu. Blade Changeable spring	Alu. Blade Spring preload	Alu. Blade	Alu. Blade (straight) Dropout pitch 100mm	Alu. Blade
Spring	Coil with bumper	Coil with bumper	Coil with bumper	Coil with bumper	Coil with bumper	Coil with bumper	Coil with bumper
Travel	30mm	35mm	35mm	30mm	35mm	30mm	40mm
Fork offset (mm)	43mm	43mm	43mm	43mm	43mm	38mm	45mm
Fork height (mm)	475	470	473.5	478.5	473.5	355	495
Brake Type	Disc & V-brake (Optional Roller Mount)	Disc & V-brake (Optional Roller Mount)	Disc only or Disc & V-brake (Optional Roller Mount)	Disc only or Disc & V-brake (Optional Roller Mount)	Disc only or Disc & V-brake (Optional Roller Mount)	Disc & V-brake	Disc only (Optional Roller Mount)
Disc Brake Mount	IS	IS	POST	POST	POST	IS	IS
Recommended Max.& Min. Rotor Size in mm	Max:160 / Min:140	Max:160 / Min:140	Max:180 / Min:160	Max:180 / Min:160	Max:180 / Min:160	Max:160 / Min:140	Max:160 / Min:140
Weight (kgs) (w/steerer at 200mm)	1.33	1.33	1.65	1.70	1.70	1.32	1.70
Max Tire (w/o fender)	700x45C	700x45C	700x50C	700x50C	700c	20"x1.5"	700x47C
Origin of Production	Taiwan	Taiwan	Taiwan	Taiwan	Taiwan	Taiwan	China

RST GLOBAL NETWORK

- RST Global office
- RST Global distributors
- RST EUROPEAN
TEST CENTRE SINGLTREK



RST

DISTRIBUTORS

: ARGENTINA

Carlos Karabitian
T 54-351-4936060
F 54-351-4931003
M carlos@karabitian.com.ar

: AUSTRIA

Thalinger Lange GmbH
T +43 7242 497 - 0
M mail@thalinger-lange.com

: BENELUX

Buzaglo B.V.
P 31-36-52-10-100
M info@buzaglo.nl

: BULGARIA

Nikol Bike Center Ltd
P +359 89 5460025
M giono.gionov@bikecenter.bg

: CENTER AMERICA

**Distribuidora
Ochenta Y Seis S.A.**
P 506 4035 2000
M gmendez@d86group.com

: CHILE

Andes Industrial Ltda.
T 56-2-265-03100
F 56-2-719-1136
M andes@andesindustrial.cl

: COLOMBIA

Len Importaciones S.A.S
T 577-6712222
M silvia.romero@lenimp.com

: CHINA

**Suzhou Dawei
Precision Co., Ltd.**
T 400-008-0698
F 0512-86160100
M sales2@rst-topway.cn

: CZECH

**Universe
Agency spol. s.r.o**
P 420-244-990-777
M info@author.cz

: ESTONIA

VELOPLUS
T +372 6556 974
M info@veloplus.ee

: FRANCE

**RST-Paul Lange
France SARL**
P +33 388 93 - 2101
M info@paul-lange.fr

: GERMANY

Paul Lange & Co.
P +49-711-258802
M info@paul-lange.de

: GREECE

**Nikos
Maniatopoulos S.A.**
P 30-2610-993045
F 30-2610-990424
M info@idealbikes.net

: HUNGARY

Velobike Kft.
P 36-1-455-8010

: ISRAEL

Ranofun
T +972-4-9522334
P +972-545600212
M ranofun@gmail.com

: ITALY

GB Center
T +39 0423 040110
M gbcenter@tiscali.it

: PHILIPPINES

Comet Cycle Center
T +63 28372-5590
F +63 23725590
M comet@cometcycle.com

: POLAND

Velo Sp. Z. O. O.
P 48-32-330-67-00
M informacja@velo.com.pl

: PORTUGAL

Motokit
P 351-234-625607
M motokit@motokit.com.pt

: RUSSIA

Maximum Ltd.
P +7-812-740-79-62
M maximum@msgbox.ru

: RUSSIA

Arves Market Ltd.
P +7-499-153-0721
P +7-495-991-6888
M arvesmarket@yandex.ru

: SPAIN

Matxcycle S.L
P +34 943 340415
M pedidos@mycycle.eu

: SWITZERLAND

Fuchs-movesa AG
P +41 56 464 46 46
M info@fuchs-movesa.ch

: SLOVAK REP.

Universe Slovakia s.r.o.
T +421-32-6521902
M author@author.sk

: TAIWAN

**RST Greenergy
Technology Co. Ltd.**
T 886-2-8521-2351
F 886-2-8521-6159
M rst@rst.com.tw

: THAILAND

Asiabike
T 084-718 3392
M info@asiabike.com

: U.S.A

**Risse Racing
Technology, Inc**
P 541-526-7242
M sales@risserracing.com

RST

GLOBAL NETWORK

RST
TAIWAN

HEAD QUARTER

RST GREENERGY TECH. CO., LTD.

TEL : +886.2.85212351

Email : rst@rst.com.tw

RST
EUROPE

RST EUROPE OFFICE

TEL : +49.711.2588255

Email : info@rst-europe.eu

RST
CHINA

SUZHOUN DAWEI PRECISION CO., LTD.

TEL : +86.512.86160698

Email : sales2@rst-topway.cn

www.rstsuspension.com

